Pur miture 309

BOQ OF TABLES CHAIRS & OTHER LOOSE FURNITURE ITEMS TO BE PROVIDED FOR INDIAN BANK RMPC BHAGALPUR

S.L	ITEM DESCRIPTION	UNIT	QTY	RATE (Rs)	AMOUNT (Rs)
1.0	WOODEN TABLE FOR CHIEF MANAGER Made out of 19 mm thick BWR ply wood for writing top	each	1		
	and vertical sides of storage unit. Front Apron of 12 mm thick BWR Ply wood with drawers' key board shelf and C P U stand. All exposed visible surfaces of table like working top, front apron drawers etc shall be finished with laminate 1 mm thick. The framing shall be provided where ever necessary. The rest of the exposed inside surfaces of the table drawers etc shall be finished with two coats of enamel paint (vanilla cream, code 3229 of Asian paint) over a coat of primer of approved make The drawers' box shall have three drawers of size 1'-6" x 2'-0" of equal height each. The key board shelf shall be of 2'-0" x 2'-0" size. All the drawers box and the shelf for the key board shall be made of 12 mm thick BWR ply wood of approved make and shall be provided with metal telescopic channels. Godrej multipurpose lock and S S finished oxidized hardware like handles, cabinet hinges etc of approved make. Wire manager shall be provided in table top. Skirting and bands shall be provided in 1 mm thick laminate of approved make and shade as directed by Architect. The height of the writing top is 2'-6" and width 3'-0"				
2.0	SIDE UNITS				
	Providing and erecting in position side/ back cabinet units with sliding shutters of approx size of 1'-3" deep x 2'-6" high made of 19 mm thick BWR grade ply wood including intermediate shelves as per Drawing / instructions. Exposed ply wood surface shall be finished with 1 mm laminate sheet of approved shade and make. Inner faces of sliding shutters shall be polished in approved colour. Free edges of ply wood shall be provided with 0'- ½" thick teak wood beading finished with N C lacquer polished. Inner faces of cabinet units shall be finished with two coats of enamel paint (Vanilla cream code 3229 of Asian paint) over a coat of primer of approved make. Quoted rates shall include cost of necessary hardware, viz handles, locks with keys in duplicate etc.	Sft	7.5		



	NOTICE BOARD				
	Providing & Fixing in position notice board as per drawing and confirming to the following specifications Basic Frame Work Well seasoned hard wood section treated with two coats of wood preservatives minimum 0'-2" x 0'-1" at suitable horizontal vertical spacing not exceeding 2'-0" c/c Skin Membrane 4 mm thick BWR grade ply wood over which 12 mm thick approved quality soft board clayed with fabric of approved shade and quality Edge Molding All free edges shall have polished 2 nd class teak wood	No	1		
	moulds of approved shape (finished 0'-2" x 0'-1") sections) with equal spirit polish in mat finish				
0	Providing and fixing cheque writing desk made out of approved 19 mm thick BWP ply frame work for side bottom and 2'-6" high pedestal, 12 mm thick Modi make Plain Glass with molding shall be fixed on vertical support of 12 mm plain glass every 6" c/c as detail drawing & instructions. A pedestal made of 19 mm thick BWP ply wood for sides shelf and bottom and 6 mm thick BWP ply wood of approved make for the back finished with 1 mm thick laminate of approved make and shade and French polish on back side shall be provided underneath the writing desk with two equal compartments having two separate lockable shutters made of teak wood frame and 6 mm thick clear glass 0'-5" wide slit shall be kept in each shutter. The bottom shelf shall be provided 0'-3" above the floor level. Skirting shall be provided in 1 mm thick laminate of approved make and shade. Writing desk size; 2'-6" x 1'-6"	No	0		
5.0	TEAK WOOD STOOL 1'-4" x 1'-4" square in size made of 15 mm thick BWR plywood finished with 4 mm thick veneer pasted with fevicol and duly polished. The frame and legs of the stoo should be of teak wood finished with French polish	No			



6.0	Providing and fixing electrical panel board area shutters with box made out of teak wood frame work, 12 mm thick BWR ply wood and 1 mm thick laminate finished on front, brass hinges handles etc and as per details. Cut outs (size 1'-0" x 2'-6" x 2 no 0 shall be provided with aluminum grill # 009/101 powder coated in approved shade in the front shutter. All inside surface shall be finished with French polish. Fixed wooden box made of the same specifications as above shall be provided. Skirting and band shall be provided in 1 mm thick laminate of approved make and shade as directed by the Architect Size 3'-0" x 1'-3" x 4-0"	Sft	0	
7.0	GLASS FOR MANAGER TABLE TOP Providing and fixing 12 mm thick floating Glass with polished crystal edge finished etc on Manager table top as per direction of Architect Size (5'-6" x 3'-0" x 1 no)	Sft	18	
8.0	DRESSING TABLE FOR LOCKER ROOM Made out of 12 mm thick BWR plywood of approved make for shelf finished with 1 mm thick laminate of approved make and shade. Back side of the shelf shall be finished with French polish. The border of the shelf shall be provided with 12 mm thick teak wood beading polished in natural shade. 5 mm thick Belgium mirror glass (size 1'-0" x 4'-0") shall be provided on 6 mm thick BWR ply wood and necessary clips etc. complete	No	0	
9.0	DRESSING STOOL Matching with Dressing table of size 1'-4' x 1'-4" with 15 mm thick BWR ply wood of approved make for top finished with 1 mm thick beach wood laminate pasted with fevicol. The frame and legs should be dully finished	0	0	



INTERIOR DESIGN AND FURNITURE WORKS FOR ALLAHABAD BANK BARSOI BRANCH, KATIHAR

S.L	ITEM DESCRIPTION	UNIT	QTY	(Rs)	AMOUNT (Rs)
10.0	FALSE CEILING				
	Providing & Fixing in position gyp/Armstrong 2'x2' Board false ceiling in two levels as per design, including necessary framework of galvanized steel members, Complete with recommended fillers, paper tapes & applying two coat of primer strictly as per manufacturer's specifications. Rates to include cost of marking opening for ceiling mounted electrical/air-conditioning accessories as per instruction. (Item to be restricted to Banking Hall & Manager's cabin Only.) (The Contractor is to submit manufacturers test report along with the measurement)	Sft.	1295		
11.0	WOODEN PANELLING				
	Wall paneling/column encasing (up to table height) works as per drawing & conforming to the following specification (Quantity/location should be restricted only to the central pillars in Banking Hall or any prime location) Basic Frame Work: Well seasoned hardwood sections, treated with two coats of wood preservatives, minimum 0'-2" x 0'-1", at suitable horizontal/vertical spacing not exceeding 2'-0" c/c. Skin Membrane: 6 mm thick BWR grade plywood with grooves formed as	Sft.	130		
	desired as per drawing/instructions Finishing: 1 mm thick laminate sheet of same or combination shades as per instructions. Skirting: 0'-4" high x 0'-1/2" thick polished 2 nd class teak wood				
	skirting with NC lacquer finish Quoted rates teak shall include all necessary materials, accessories & labor & also allow provisions for electrical/telephone/computer wiring conduits & switch				
	boxes .(Material for wiring conduits & switch boxes shall separately paid for.) Coloumns paneling — 5'-0"x 8'6"x 1Nos.				



12.0	PARTLY GLAZED FULL HEIGHT WOODEN PARTITIONS FOR C. MANAGER CHAMBER				
	Supplying & erecting full height Partition partly glazed wooden partitions for Manager Chamber, Store Room and Clerical Counters as per drawing and conforming to the following specifications Basic Frame Work Well seasoned Malaysian hard wood section treated with two coats of wood preservatives 2 ½" x 1 ½" (minimum) at maximum 2'-0" horizontal or vertical spacing as per site conditions. Vertical Members shall be suitably anchored at floor & ceiling level to ensure rigidity. Exposed frame members in the glazed portions shall be wider spacing (approx 6'-0") or as per instructions Exposed members shall be finished with 1 mm thick laminate sheet of same or combination shade over 6 mm BWR plywood facing including4 x 6 mm grooves at location as per instructions Skin Membrane Opaque portion up to 3'-0" from floor level and from false ceiling from floor level with 2 x 6 mm thick BWR grade plywood on each face. With Groove formed at the top layer as per drawing/ instructions Finishing 1 mm thick laminate sheet of same or combination shades as per instructions. Skirting 0'-4" high x 0'-1/2" thick polished teak wood skirting with NC lacquer finish Glazing 6 mm thick clear float glass fixed with continuous steam beech wood glazing beads of approved shape (finished 0'-1	Sft.	115		
	beech wood glazing beads of approved shape (finished 0'-1 %" x 0'-1") all round polished and coated with NC lacquer finish. The rate should also include cost for decorative itching on one side of the glass				
	Near common toilet door (one partition of cabin 7)	Sft.	77		
13.0	FULL HEIGHT NON GLAZED PARTITION: Providing and fixing full height wooden partition				



	(server room & near locker room gate) with frame of 2"x2" (finished size) seasoned hard wood member at max intervals of 1'-6" x1'-6" c/c with provision of bigger at skirting, fixing to the ceiling, slab, beams etc including the door of size 3'-0"x7'-0". All woodwork to be treated with 1st quality anti termite paint and should be covered with 6 mm thick ply Board of approved make finished by 1.0 mm thick laminate of	Sft	0	
14.0	FLAP GATE Made out of Sal Wood /Chill Wood frame 0'-2" x 0'-2" and 6 mm thick BWR plywood on its both sides finished with 1 mm thick laminate pasted with fevicol Edges of the top gate finished with teak wood beading polished in natural shade. The gate shall be provided with Oxidized M S hinges and door springs. Skirting and bands shall be provided in 1 mm thick laminate of approved make and shade as directed by Architect. Size: 3'0"x4'6"x1nos	Sft	0	
15.0	Made out of 19 mm thick BWR plywood for working top keyboard shelf and vertical sides of counter and stronger unit front apron of 19 mm thick BWR ply with four 1'-6" wide drawers (of equal height) on the right side shall be provided. Division shall be made in appropriate sizes in drawers to store currency notes of different denominations and different sizes. Customer hand rest 1'-3" wide and 1'-0" high made of 12 mm thick BWR plywood for the vertical surface and the top shall be provided. ¾" thick polished jet black granite with beveled edges shall be provided above the working top and customer top. 19 mm thick and 2'-0" wide plywood of approved make shall be provided 0'-3" above floor level and across the counter for CPU shelf and foot rest. All exposed visible surfaces of counter like working top, front apron, drawers etc shall be finished with 1 mm thick laminate of approved make and shade. The key board shelf shall be 2'-0" x 2'-0" size and provided with teak wood beading polished natural. The rest of the exposed inside surface of counters drawers etc shall be finished with two coat of enamel paint (vanilla, cream, code 3229 of Asian Paint) over a coat of primer of approved make. Height and width of the writing top shall be 2'-6". Height of the customer hand rest shall be provided with Godrej	Rft	0	



	Multipurpose locks, metal telescopic channels and S S finished oxidized handles(0'-3") and hardware Skirting and bands shall be provided in 1 mm thick laminate of approved make and shade as directed by Architect			
16.0	OFFICERS COUNTERS (EXECUTIVE TABLES)			
	Made out of 19 mm thick BWR plywood for working top keyboard shelf and vertical sides of counter and stronger unit front apron of 19 mm thick BWR ply with four 1'-6" x 0'-6" wide drawers (clear dimension) removable shelf and cupboard with shutter on the right side shall be provided. The writing top shall be provided with ½" thick polished jet black granite with beveled edges shall be provided above the working top and customer top. 19 mm thick and 2'-0" wide plywood of approved make shall be provided 0'-3" above floor level and across the counter for CPU shelf and foot rest. All exposed visible surfaces of counter like working top, front apron, drawers cupboard fascia etc shall be finished with 1 mm thick laminate of approved make and shade. The key board shelf shall be 2'-0" x 2'-0" size and provided with teak wood beading polished natural. The rest of the exposed inside surface of counters drawers etc shall be finished with two coat of enamel paint (vanilla, cream, code 3229 of Asian Paint) over a coat of primer of approved make. Height and width of the writing top shall be 2'-6" and 2'-9" each The Drawers and shutters shall be provided with Godrej Multipurpose locks, metal telescopic channels and S S finished oxidized handles(0'-3") and hardware Skirting and bands shall be provided in 1 mm thick laminate of approved make and shade as directed by Architect			
а	Officer table (5'-0" x 2'-6'x 12nos.)	each	12	
b	Officer table (4'6"x2'-6"'x 2nos.)	each	2	
С	Side Credenza (3'0"x2'6")	each	14	
d	low height storage	Sft	124	
17.0	CASH CABIN PARTITION			
	Made out of 2" x2"(clear size) Sal wood chill wood members placed at not more than 2'-0" distance both ways and 6 mm thick BWR ply board of approved make finished with 1 mm thick laminate of approved make and shade on both sides. Skirting and bands shall be provided in the partition as			



18.0	directed by Architect An opening of 8" x 4" at 3'-0" height with 8" x 8" tray made of 12 mm thick BWR plywood of approved make finished with 1 mm thick laminate of approved make and shade on all four sides shall be provided wherever required The partition shall have aluminum grill # 009/101 of approved make and powder coated in approved colour in wooden frame from 3-9" height to 7'-0" height A Door shutter made of same specification and finished with 1 mm thick laminate of approved make and shade shall be provided in the partition with Godrej make S S finished cylindrical lock S S heavy duty hinges and door closer of approved make shall be provided in the shutter. Size: 7'0"x7'0"x3Nos., 11'0"x7'0"x1 Nos.[include door] Door size: 2'6"x7'0"x 2Nos. FRONT PARTITION FOR CASH CABIN AND SINGLE WINDOW	Sft.	0
	12 mm thick clear float glass partition from top of the customer hand rest to 6'-9" height fixed with the side wooden partition. A semicircular opening (0'-8" dia) and 0'-2" wide slit shall be provided in the partition as directed by the Architect	Sft.	0
19.0	FRONT PARTITION FOR COUNTERS 12 mm thick clear float glass partition along with 1'-0" wide 12 mm thick clear float glass horizontally placed above it shall be provided in front of the clerical counters. 0'-2" wide slit shall be provided in the partition at the bottom. Total height of partition along with the horizontal glass member and slit is 1'-3". The glass partition shall be fixed with 0'-2" x 0'-2" wooden posts 1'-3" high and finished with 1 mm thick laminate of approved make and shade Size: 6'10"x1'3"x1nos, 7'5"x1'3"x1nos.	Sft	0
20.0	ROLING SHUTTER BOX. Providing and fixing Rolling shutters boxes made out of 2" x 1 ½" size teak wood frame work. 19 mm thick BWR plywood open able door etc, complete with enamel paint finish of approved quality & shade as per instruction 9'x1'6"x2Nos., 9'x2'0"x1Nos., 2'0"x1'6"x2Nos.	Sft	55
21.0	Providing Factory made Aluminum Main Entrance Door of INDAL / Jindal sections minimum section thickness of 2.5 mm all complete with swing door, fixed portion all 12 mm	Sft	55



	thick glass, coloured anodized / powder coated as per standard approved sections, all complete with all necessary hardware and fittings, including floor springs, door lock etc.		
22.0	CHEQUE DROP BOX Providing and fixing one suggestion box, made with 12 mm ply as per standard design and specification of the Bank fully complete with enamel painting, lock, lettering on top etc.	Each	0
23.0	Providing and fixing Cheque writing / slip rack projected/ supported from wall 6'-0" x 1'-3" and a C T as per design with suggestion box first aid box.	Each	0
24.0	SUGGESTION BOX Providing and fixing one suggestion box made with 12 mm ply as per standard design and specification of the Bank fully complete with enamel painting, lock, lettering on top etc	Each	0
25.0	Clerical counter top Black Granite 18 mm Key Board, Drawers, C P U Stand water proof B W R Grade or B W P plywood Alpo, Green century	Sft	0
26.0	Providing and fixing Doon box set on cash counter (godrej make)	each	0
	TOTAL		

