B.O.Q OF INTERIOR FURNISHING WORK FOR INDIAN BANK E-LOBBY AT BERHAMPUR.							
Sl. No.	Particulars Particulars	Units	Qnty.	Rate. (Rs)	Amount. (Rs)		
1.0	Doors & glazed partition.						
	Providing and fixing Entrance Door (glazed) as per						
	drawing in black Anodised aluminium door single						
	groove section of size 125mmx25mm (Jindal make)						
	in top and bottom & sides glazed with 10 mm thick						
	glass of approved make . Item to include all						
	necessary hardware of Stainless Steel finish and						
	chemical eaching with bank's logo as approved by the						
	Project Consultant/Bank complete in all respects.						
	a) Open able portion (it include SS finished H type 1'	Sft	24.50				
	6" long door handle)						
	b) Fixed portion	Sft	60.00				
2.0	Floor spring						
	Providing and fixing Godrej make heavy duty floor	Nos	1.00				
	spring in entrance door with necessary fixtures and						
	fittings etc.						
3.0	False ceiling (Gypsum board.)						
	Providing & fixing at site plain Gypsum Board false	Sft	95.00				
	ceiling made out of 12.5 mm thick paper reinforced						
	gypsum board sheets to be fixed with main frame						
	channels of size(80 mm x 26 mm x 0.5 mm) at every						
	450 mm c/c, intermediate channels of size(15 mm x						
	45 mm x 0.9 mm) at every 1220 mm c/c with						
	perimeter channel 20 mm x 26 mm x 0.5 mm all						
	along the wall shall be provided . The frame work to						
	be suspended with strap bolts as recommended using						
	rail plugs 12.5 mm dia x 35 mm long with 6 mm dia						
	bolt and soffit cleat. Ceiling surface is to paint with						
	two coats of distemper to get a smooth & even look						
	including the cost of hard ware fittings, all labour &						

Sl. No.	Particulars Particulars	Units	Qnty.	Rate. (Rs)	Amount. (Rs)
4.0	Faceade cliding (ACP)			(143)	(143)
	Providing and fixing in position almunium composit panel boxing with PVDF coating & LDPE core laminated Eurobond/Altobond/Alukbond Exterior grade 4mm thick including fabrication for the same with almunium sections, required hard ware, silicon sealent (Dow coming 789), masking tape, necessary scafolding etc. It also include the trap door shutter with magnetic catch. The work should be completed		100.00		
5.0	Full glazed Partition				
	Providing, fitting & fixing 12mm thick flot glass partition with chemically eaching as per design.the partiton will be supported with S.S patch panel fittings as per drawing and design. The exposed edge of the glass partition should be polished to super quality. The work should be completed as per direction of architect including cost of all labour & material		15.00		
	TOTAL			Rs:-	

Total Amount In Words:-