



**PREMISES DEPARTMENT
ZONAL OFFICE KANPUR**

**TENDER DOCUMENT
INTERIOR FURNISHING WORKS IN NEW PREMISES OF
INDIAN BANK –LAJPAT NAGAR BRANCH, DISTRICT – KANPUR NAGAR**

PART II – FINANCIAL BID

**Ref:No : ZOK:PRM:2022-23:05
Date : 10/06/2022**

Issued to:

.....
.....
.....

Last date for submission of Bid	20/06/2022 upto 15:00 HRS at Indian Bank, Zonal Office, Premises Department, 15/287, Civil Lines, Mall Road, Bada Chauraha, Near Z-Square Mall, Kanpur - 208001
Date of Opening of Technical Bid	20/06/2022 at 16:00 HRS Indian Bank, Zonal Office, Premises Department, 15/287, Civil Lines, Mall Road, Bada Chauraha, Near Z-Square Mall, Kanpur - 208001
Date of Opening of Financial Bid	To be intimated separately to the Firms Qualifying in Technical Bids

CONSULTANT:

**M/s Bharat and Associates
Kanpur Office - Flat No : J-19, 4TH Floor, Block – J,
Indraprasth Apartment, Ratanlal Nagar
Kanpur – 208022**

**Mobile No : 7572003109, 7572003101
Email – bharatandassociateslko@gmail.com**

SCHEDULE OF QUANTITIES

TENDER FOR INTERIOR FURNISHING WORK IN NEW PREMISES OF INDIAN BANK – LAJPAT NAGAR BRANCH, DISTRICT – KANPUR NAGAR					
S.NO	DESCRIPTION OF ITEM	UNIT	QUANTITY	RATE PER UNIT (Rs.)	AMOUNT (Exclusive of GST) (Rs.)
1.0	SUSPENDED FALSE CEILING				
1.1	GYPSUM FALSE CEILING WITH COVE				
	Providing, fabricating and erecting in position totally flushed suspended false ceiling with 12.0mm thick Gypsum board, fixed to a metal frame work comprising of ceiling channel of size 80mmx26mmx0.5mm @ every 457cm centre, inter channel 45mmx15mmx0.9mm @ every 1220 cm centres, peri-meter channel 20mmx26 mm all along the wall/partitions, strap hanger suspenders 25mmx0.5mm with nuts and bolts 6.4mmx12.7mm, connecting clips 2.6mm thick, dry walls screws 25m long, soffit cleats 27mmx37mmx25mmx1.6mm thick and dash fastenes / rawl plugs 12.5 mm diax35mm long with 6mm dia bolts etc. complete with recommended fillers, paper tapes and applying two coats of acrylic emulsion paint of approved shade and make over a coat of primer including making necessary cut outs for light fittings/ ACs etc. complete as per manufacture's specifications. (Quantity as per layout plan/site requirement)	Sq.ft	780.00		
1.2	FALSE CEILING (ARMSTRONG CEILINGS – FINE FISSURED MICROLOOK EDGE WITH SILHOUETTE GRID (BLACK REVEAL))				
	Providing and fixing false ceiling system manufactured by M/s. Armstrong World Industries using hot dipped galvanized steel section, rotary stitched main tee of size 15mm x 42 mm web height, having 0.36 mm gauge at every 600 mm centre to centre maximum and rotary stitched cross tee of size 15 mm x 42 mm, having 0.33 mm gauge at every 600 mm. c/c. and wall angle of size 19 x 19 mm., having 0.35 mm gauge fixed to the periphery of the wall. The above grid is suspended at every 600mm c/c. in both directions using 2.0 mm. thick pre-straightened GI wire laying FINE FISSURED MICROLOOK WITH SILHOUETTE GRID(BLACK REVEAL) ceiling tiles manufactured by M/s. Armstrong World Industries, of size 600mmx600mmx15mm having NRC 0.55, Light reflectance of >84% (WT), thermal conductivity k = 0.052-0.057 W/m0K, Humidity Resistance of 99% , having Fire Performance CLASS O / CLASS 1 (BS 476), surface having 3 coats of white paint with Fine Fissured, back of the tile duly sanded and finished	Sq.ft	660.00		

	with a coat of protective paint.				
1.3	Designer MDF board false ceiling/Pillars 12mm thick with CNC Cutting and backing of Acrylic /Metalim, Equivalent as per direction of the architect. The support system to be as above.	Sq.ft	200.00		
2.0	WALL PANELLING & COLUMN ENCASING WITH DIFFERENT LEVEL INSTRUCTION AS PER ARCHITECT				
	<p>Supplying and erecting Wall paneling / Column encasing (up to false ceiling) as per drawing and design and conforming to the following specifications :</p> <p>Basic frame work: Framing shall consist of Heavy duty Aluminum Box Sections 50mm x 50mm x 2 mm thick @ 600mm c/c both ways Horizontally and Vertically. The vertical alternate frames to be fixed to the ceiling with necessary fixtures. Vertical members shall be suitably anchored at ceiling level to ensure rigidity.</p> <p>Skin membrane : 9 mm thick BWP grade plywood on face.</p> <p>Finishing : 1.0mm thick laminate sheet of same or combination shades with grooves as per instructions.</p> <p>Skirting: 100mm high laminate of approved make & shade all as directed.</p> <p>Top Border: 150mm high laminate of approved make & shade all as directed.</p> <p>Note: Quoted rates shall include all necessary materials, accessories and labour and also for making provisions for electrical/telephone/computer wiring, conduits and switch boxes, etc. where ever required. (quantity/location should be restricted only to the central pillars in Banking hall/to hide electrical pipes/AC drain pipes/any prime location)</p>	Sq.ft	500.00		
3.0	PARTITIONS				
3.1	CASH CABIN PARTITIONS : Supplying & Erecting full height solid cash cabin partitions (upto false ceiling as per following specifications : Basic frame work: Framing shall consist of Heavy duty Aluminium Box Sections 50mm x 50mm x 2 mm thick @ 600mm c/c both ways Horizontally and Vertically. The vertical alternate frames to be fixed to the ceiling with necessary fixtures. Vertical members shall be suitably anchored at ceiling level to ensure rigidity. Skin membrane: To be finished with 12 mm thick BWP grade plywood on each face with grooves, as per drawings/ instructions. Finishing: 1.0mm thick laminate of same or combination shades with grooves in both faces as per	Sq.ft	220.00		



	<p>instructions. Skirting- 100mm high laminate of approved make & shade all as directed. Top Border: 150mm high laminate of approved make & shade all as directed. It shall have decorative aluminum grill (from 1200mm to 2100mm) fixed with teak wood beading (size – 30mm x 20mm, as per profile) with melamine finish. The job shall also include for provision of laying conduits, switch boxes etc. The erection of partition shall include for expansion bolts cleats, clamps bolts, nuts, screws, rivets and other accessories, all complete up to the satisfaction of the Architect. All door opening shall have rebated teak wood framework (size – 75mm x 50mm, as per profile) on vertical (2 Nos.) and horizontal (1 No.) sides, with melamine finish and rebate of 40mm x 12mm, all complete up to the satisfaction of the Architect. Quoted rates shall include all necessary materials, accessories and labour and also to make provisions for electrical / telephone / computer wiring conduits and switch boxes, etc. (Materials for wiring, conduits, switches etc. shall be separately paid for)</p>				
<p>3.2</p>	<p>Supplying and erecting full height partly glazed / unglazed partitions as per following specifications:Basic frame work: Framing shall consist of Heavy duty Aluminum Box Sections 50mm x 50mm x 2mm thick @ 600mm c/c both ways Horizontally and Vertically. The vertical alternate frames to be fixed to the ceiling with necessary fixtures. Vertical members shall be suitably anchored at ceiling level to ensure rigidity. Exposed frame members in the glazed portions shall have wider spacing (approx. 1200 mm) and be finished with 1.00 mm thick laminate of same or combination shades, over 6mm BWP grade ply.Skin membrane: (Opaque portion up to 900mm from floor level and from 2100mm to ceiling, finished with 12 mm thick BWP grade plywood on each face with grooves, as per drawings/ instructions.Finishing: 1.0mm thick laminate of same or combination shades with grooves as per instructions.Glazing: 12mm thick clear float glass fixed with polished teak / steam beech wood glazing beads of approved shape (finished 12 x 25mm). Skirting- 100mm high laminate of approved make & shade all as directed.Top Border: 150mm high laminate of approved make & shade all as directed.Quoted rates shall include all necessary materials, accessories and labour and also to make provisions for electrical / telephone / computer wiring conduits and switch boxes, etc. (Materials for wiring, conduits & switches etc. shall be separately paid for)</p>	<p>Sq.ft</p>	<p>180.00</p>		



<p>3.3</p>	<p>Supply and erecting low height opaque partitions (up to maximum 1200mm height) conforming to the following specifications : Basic frame work: Framing shall consist of Heavy duty Aluminium Box Sections 50mm x 50mm @ 600mm c/c both ways Horizontally and Vertically. The vertical alternate frames to be fixed to the ceiling with necessary fixtures. Vertical members shall be suitably anchored at ceiling level to ensure rigidity. Skin membrane: 12 mm thick BWP grade ply on each face up to 900mm height. Glazing: 12mm glass in remaining portion, Finishing: 1.0-mm thick laminate of same or combination shades with grooves as per instructions. Edge moulds: All free top/ end surfaces shall have polished teak / steam beech wood moulds of approved shape (from 18 x 50mm sections). Skirting- 100mm high laminate of approved make & shade all as directed. Quoted rates shall include all necessary materials, accessories and labour and also allow provisions for electrical / telephone/computer wiring, conduits and switch boxes, etc. (Materials for wiring, conduits and switch boxes shall be separately paid for.)</p>	<p>Sq.ft</p>	<p>50.00</p>		
<p>4.0</p>	<p>COUNTER & WORK STATIONS</p>				
<p>4.1</p>	<p>Providing and erecting in position Cash Work Station of approx. size 1370x900x750mm (4.5'x3.0'x2.5'), made of 19mm thick block board pasted with 1.00mm laminate inclusive of a 350mm wide customer top at 1155 mm level. Writing top & customer top should be finished with mirror polished; 18mm thick granite slab (Jet black or shade as directed by Bank's Engineer) with rounded edges and sides with 1.0mm thick laminate of approved shade/make. Both should have sufficient gap in between to accommodate computer monitor up to full depth. The workstations shall be supported from the partition system made of 19mm thick BWP grade block board finished with 1.00 mm thick laminate of approved shade/make. Free edges shall have 18 mm thick, polished white or steam beach wood moldings of half-round profile as per drawings and instructions and 100mm high laminate of approved make & shade all as directed. Each cash workstation shall comprise of the drawer unit, Tea tray at top, Cash drawers with approved telescopic channels for drawer-slides, automatic locks (keys in duplicate), wire managers, space for computer CPU, modesty panel and other necessary hardware and accessories including satin finish S. S. handles of approved quality. Inner face of cash counter to be provided with 16G, M.S. sheet, painted with two coats of synthetic enamel paint of approved shade & make, over a coat of approved steel primer. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer.</p>	<p>R.ft</p>	<p>10.00</p>		

	Skirting: 100mm high laminate of approved make & shade all as directed.				
4.2	<p>GLASS BARRIER ON CASH CABIN / OFFICER COUNTER Providing & fixing 12mm thick clear float glass on Cash Counters at front & sides, with S S clamps/patch fittings, necessary polished beadings etc complete all as directed by the Bank.</p> <p>Note: Front glass to be fixed in slanting position towards inside cash area with required angle as directed. Above glass to be fixed either in two pieces. Lower piece having one semi-circular/rectangle 6” dia/long opening at customer top level & other piece to be fixed at suitable height making 3” slit for conversation with customer. In this case, only glass area to be measured for payment purpose.) In case of single piece, one semi- circular/rectangle 6” dia/long opening at customer top level & one circular hole of required dia at suitable height for conversation at centre of cash counter to be provided.</p>	Sq.ft	100.00		
4.3	<p>ALUMINIUM JALI ON CASH CABIN TOP Providing and fixing of aluminum grill with square size 75mm x 75mm – 8mm, on top of the cash cabins etc. The grill shall be tightly stretched and nailed to a wooden frame work, made out of 50mm x 40mm teak/hard wood (with anti-termite) members at 750mm c/c approx. both ways or as per site conditions. The erection of framework shall include for expansion bolts cleats, clamps bolts, nuts, screws, rivets and other accessories. All teak wood surfaces shall be painted with two coats of synthetic enamel over one coat of primer. The rate shall include cost of all materials, labour, T&P, wastages, etc. required for proper completion of work, all complete to the satisfaction of the Bank.</p>	Sq.Ft.	70.00		
4.4	<p>OFFICER COUNTERS / LOW LEVEL COUNTER Supplying and erecting counters (running tables) 915 mm wide and 750mm high including drawer-cum- cabinet unit for files, space for computer CPU, wire managers, modesty panel, tea tray etc. made with 19mm thick BWP grade block board on top and supporting sides / front with necessary well seasoned Malaysian Sal/ Kail/ Mirandi wood frame work. Writing top & customer top should be finished with mirror polished; 18mm thick granite slab (Jet black or shade as directed by Bank's Engineer) with rounded bevelled edges and sides with 1.0mm thick laminate of approved shade/make finished on sides with 1.0 mm thick laminate of approved shade and quality, including providing and fixing 450mm long key board tray of approved shade, hardware and accessories at each of the counter. All exposed edges of block board are to be provided with half round teak wood mouldings, duly polished and 100mm high laminate of approved make & shade all as directed. Customer Top will be raised by 6 inches to provide a box type formation in the front elevation. Inner faces</p>	R.ft	20.00		

	shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer.Skirting: 100mm high laminate of approved make & shade all as directed.Rate to include charges for brass hardware fittings as well as fixtures like sliding gear for drawers of 'Earl Behari' or equivalent approved make.(ELEVATION DESIGN OF COUNTER WILL BE PROVIDED BY ARCHITECT AS PER SITE CONDITION)				
5.0	DOORS				
5.1	Supplying and fixing in position overall 32 mm thick solid core hot pressed phenol formaldehyde bonded flush door finished with 1.0 mm thick laminate of approved shade and quality on both sides of the door shutter & beading on edges including cost of hardware fittings e.g. Godrej night latch / mortise lock, hinges, door closure, handles etc. of approved make and quality. (CASH CABIN) . Please note that the price must include providing and fixing aluminum grill with square size 75mm x 75 mm in the door as per Bank's instructions with grill tightly stretched and nailed to wooden framework along with steam beach wood beads of approved design complete for Cash Cabin Door as per Bank's instructions	Sqft	40.00		
5.2	Supplying and fixing in position 32 mm thick solid core hot pressed phenol formaldehyde bonded partly glazed flush door shutter of approved make finished up to 900 mm from floor level with 1.00 mm thick laminate of approved quality on both sides of the door shutter & beading on edges. The upper portion of the shutter is to be provided with 12 mm thick clear float glass fixed with white or steam beech wood glazing beads of approved design, complete as per drawing. Rate to include cost of hardware fittings e.g. mortise lock, hinges, handles, door closer etc. of approved make and quality. (BM CABIN DOOR / PASSAGE DOOR / STR ROOM PASSAGE DOOR)	Sqft	91.00		
5.3	FLAP DOOR Providing and fixing Flap Door of min. size: 3' (B) X 2'6" (H) made of block board with approved lamination on both side, of required size with hinges/tower bolts/stopper/handles etc complete.	Sqft	12.00		
5.4	ENTRANCE DOOR - TOUGHENED GLASS DOOR WITH FIXED GLASS PARTITION & ETCHING WORK (2 UNITS) (DOUBLE DOOR IN EACH UNIT) Providing fabricating & fixing in position twin -style door at Main Entrance made of 12mm thick clear toughened glass (MODI / ST. GOBAIN) in single piece with computerized diamond cut and edge polish pencil edges all around including making required cut holes for lock, handles, pivot patch fitting, corner fitting , hinges , etc. Glass should be fixed in S.S finished D-Brackets, etc. Wherever required with metal patch fittings at Top / Bottom / Corner / profile section for fixed glass as approved by Bank Authorities for Door	Sqft	100.00		



	Shutter. For Glass Partition wherever required if any, the glass panels can be bolted together with stainless steel stub post which are into concrete through core drill holes or supported by stainless steel clamp fixing to vertical posts on each side as per requirement at the site with necessary bevelling etc. complete fixed on floor spring of Ozone / Dorma / Godrej Make (ISI Mark & Heavy Duty). The Door Shutters shall have C - shaped Stainless Steel Handle (18" or 24" as directed) on both the door and both the sides of approved make with erection, finishing, etc complete. The fixed glass partition are to be fixed by providing profile section @ Top & Bottom. The entire glass partition is to be finished with one way film, bank logo or as per Bank's Requirement.				
6.0	OTHER ITEMS				
6.1	LOW / FULL HEIGHT STORAGE CABINET P/F in position 450mm deep storage full ht./low ht.cabinets having sides partitions, shelves & shutters, fabricated out of 19mm BWR & 6mm th. BWR Plywood back with all exposed surfaces & inside of shutters/internal base of drawers to be finished with 1mm thick laminate i/c 31x31mm rounded steam beech wood moulding & 6x19mm steam beech wood edging on edges of comm.board as/arch.drg.complete with shelves, shutter, drawers etc. i/c P/F necessary hardware telescopic channels for drawers of Hettich , S.S.piano hinges as/appvd sample, Hettich handles(as/appvd. sample)in all drawers & shutters, locking arrangement,75mm brass tower bolts,Hettich locks in all shutters & drawers, magnet catcher, painting the exposed internal surfaces of block board with 2-3 coats of synthetic enamel paint with melamine finish on wood surface with 6mm comm.ply at rear as per arch.drg.& as per site requirements the rate should include 19mm th. pre-polished Granite Stone (Asian Quartz) as per approved sample with half round beveled edge complete on low ht. storage cabinets.	Sq.Ft.	140.00		
6.2	MAIN PANEL BOXING				
	Providing and fixing 1'4" deep electrical panel cabinet. The basic structure of cabinet includes dividers and shelves made up of 18 mm thick Bison panel sheet. It shall have openable shutters with louvers and shall be made with 2" x 1" x min 1.8mm thick aluminium section framework covered with 6mm bison panel sheet on all sides with 16 Gu.powder coated perforated S.S. Sheet as infill material. It will have 1mm laminate on outside surface as per Architect & Bank's Instructions. The entire unit shall finish with paint on internal surface. The rate includes all the hardwares, labour, scaffolding, etc complete.	Sq.Ft	80.00		



6.3	ACP PANNELING ON FRONT / ROLLING SHUTTER COLUMN	Sq.Ft	272.00		
	<p>Providing and fixing in required position 4mm thick exterior grade Aluminum Composite Panel in Ceiling and Vertical Cladding or as per requirement and directed by Bank's Engineer or Architect over a framework made out of 50 x 50 x 2 mm aluminum SHS anchored to existing M.S Structure including installing the composite panel in grid pattern of 2' x 2' or of required size as directed with the help of aluminum cleats / angles of size 1" x 1" and striking out joints with weather silicon. The rate shall include cutting of panels, its bending, cutting for providing down lighters, providing opening for operation of rolling shutters, labour, scaffolding, etc complete.</p>				
6.4	SLIDING ALUMINIUM WINDOW WITH BOMBAY SLIDERS	Sq.ft	30.00		
	<p>Providing and fixing powder coated anodized aluminum sliding window with glass along with all the hardwares complete and properly sealed with sealants and rubber gaskets to shut down any air gaps.</p>				
7.0	FIXTURES				
7.1	<p>BRANCH MANAGER TABLE WITH SIDE CREDENZA INCLUDE 12mm THICK GLASS:- Providing and placing in position tables with top, vertical sides/dividers, skirting and modesty panel made out of 19mm thick water proof board with 1mm thick laminate (as/shade approved by the Architect) on all exposed surfaces. It shall also have 75mm x 40mm teak wood runners below the top and for footrest below. Every table shall be provided with a side unit (size – W-500mm, H-750mm, D-500mm approx.), consisting of 150 mm deep drawer at top and a cabinet with open able/hinged shutter below. The facia of drawer and shutter of cabinet below shall be made out 19mm thick water proof board with 1mm thick laminate (as/shade approved by the Architect) and sides and bottom of drawer shall be made out of 12mm thick water proof ply. The side unit shall have CAM locks, handles, guides, sliding units, hinges, magnetic catcher's etc. of approved make. Every table shall be provided with a pedestal unit (size – W-550mm, H-720mm, D-450mm approx.) below. The table shall have 100mm deep facia, below the top, in which keyboard drawer unit shall be adjusted. It shall be made out 19mm thick water proof board with 1mm thick laminate (as/shade approved by the Architect) and sides and bottom of drawer shall be made out of 12mm thick water proof ply. The unit shall have CAM locks, handles, guides, sliding units etc. of approved make. The job shall include for 6mm x 6mm grooves in between sides and open able drawers and hinged shutters. All the exposed edges of water proof board and ply shall be provided with 6mm thick teak wood/hard wood lipping. All teak wood surfaces shall be melamine polished and other internal surfaces shall</p>	No.	1.00		

	be painted with two coats of synthetic enamel over one coat of primer, all complete to the satisfaction of the Architect. Every table top shall be provided with 12 mm thick float glass (as per profile) with polished and beveled (25mm wide) edges all complete to the satisfaction of the Architect. Approx size of table : 1830 x 915 x 750 mm (6.0'x 3.0'x 2.5') or 1524 x 915 x 750 mm (5.0'x 3'x 2.5')				
7.2	OFFICER TABLE WITH SIDE CREDENZA INCLUDE 12mm THICK GLASS:- Providing and placing in position tables with top, vertical sides/dividers, skirting and modesty panel made out of 19mm thick water proof board with 1mm thick laminate (as/shade approved by the Architect) on all exposed surfaces. It shall also have 75mm x 40mm teak wood runners below the top and for footrest below. The facia of drawer and shutter of cabinet below shall be made out 19mm thick water proof board with 1mm thick laminate (as/shade approved by the Architect) and sides and bottom of drawer shall be made out of 12mm thick water proof ply. Every table shall be provided with a pedestal unit (size – W- 465mm, H- 720mm, D-450mm approx.) below. The table shall have 100mm deep facia, below the top, in which keyboard drawer unit shall be adjusted. It shall be made out 19mm thick water proof board with 1mm thick laminate (as/shade approved by the Architect) and sides and bottom of drawer shall be made out of 12mm thick water proof ply. The unit shall have CAM locks, handles, guides, sliding units etc. of approved make. The job shall include for 6mm x 6mm grooves in between sides and open able drawers and hinged shutters. All the exposed edges of water proof board and ply shall be provided with 6mm thick teak wood/hard wood lipping. All teak wood surfaces shall be melamine polished and other internal surfaces shall be painted with two coats of synthetic enamel over one coat of primer, all complete to the satisfaction of the Architect. Every table top shall be provided with 12 mm thick float glass (as per profile) with polished and beveled (25mm wide) edges all complete to the satisfaction of the Architect. Approx Size : 1372 x 750 x 750 mm (4.6'x 2.5'x 2.5')	No.	2.00		
8.0	MISCELLANEOUS ITEMS				
8.1	SLIP & CUSTOMER WRITING DESK	No.	1.00		
	Providing and fixing in position (with rear wall) slip and customer writing desk (as per design) of overall size – 1200mm x 450mm x 300mm. The fixing shall include for expansion bolts, cleats, clamps, bolts, nuts, screws, rivets and other anodized accessories, all complete up to the satisfaction of the Architect.				



	<p>The writing top and facia/sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect), on all sides and . It shall be laid over the base of 19mm thick water proof board (already considered in various items.) and fixed with araldite. It shall include for beveling and polishing at all the exposed edges. The rate shall include cost of all materials, labour, scaffolding, wastages, polishing and T& P etc. It shall be made out of 12mm thick water proof plywood (two surfaces of 6mm thickness, fixed together, where required) on rear and both sides. The front shall be made out of 12mm thick glass (as per profile). It shall be fixed in the grooves, made in side members, in an inclined manner (as per profile in drawing enclosed) with a gap of 75mm (max.) in between. The space shall be further divided in four equal parts with help of 12mm thick water proof plywood. All edges of the glass shall be polished. All the exposed edges of water proof board and plywood shall be provided with 6mm thick teak wood/hard wood lipping. All teak wood surfaces shall be melamine polished and other internal surfaces shall be painted with two coats of synthetic enamel over one coat of primer, all complete to the satisfaction of the Architect.</p>				
<p>8.2</p>	<p>CHEQUE DROP BOX / SUGGESTION BOX</p>	<p>No.</p>	<p>2.00</p>		
	<p>Supplying and erecting cheque drop box / suggestion box (over all size 400mmx150mmx600mm) made of 19 mm thick BWP grade ply board and curved portion at top made out of 90mmx90mm C.P. teak/steam beach wood section. A slit opening of 10mmx150mm is to be provided at the top of the box. An openable shutter of 259mmx262mm size made of 19 mm thick BWP grade block board is to be provided.</p>				
	<p>The entire exposed timber surface including all free edges is to be finished with 1mm thick laminate sheet of combination shade. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Rate to include cost of necessary hardware fittings e.g. hinges, lock, knob, etc. of approved design and quality.</p>				
<p>8.3</p>	<p>NOTICE BOARD</p>	<p>No.</p>	<p>1.00</p>		
	<p>Providing and fixing in position notice board (as per design) of size – 900mm x 600mm x 150mm. The sides shall be made out of 19mm thick water proof board with 1mm thick laminate (as per shade approved by the architect) on all exposed surfaces.It shall have 12mm thick tack The front shall have 6mm thick float glass sliding shutter in two parts.It shall also have 19mm wide two track aluminum channel for sliding arrangement, all around, along with locking arrangement. Board (Make – Cellotex or equivalent) wrapped with stretched blazer cloth (Make-Raymonds), of Rs. 200.00 per Mt. (approx.) in colour and pattern approved by the Architect. It shall be fixed with help of kail/partal wood (sect. 19mm x 25mm)</p>				



	frame work. It shall be covered with 6mm thick water proof plywood, on the back. All the exposed edges of water proof board and ply shall be provided with 6mm thick teak wood/hard wood lipping. All teak wood surfaces shall be melamine polished and other internal surfaces shall be painted with two coats of synthetic enamel over one coat of primer, all complete to the satisfaction of the Architect.				
8.4	ETCHING WORK & BANK LOGO FOR BRANCH	LS	1.00		
	Etching for Toughened glass, Etching for Front counters / Manager Cabin.				
	Etching work on glass with chemicals (as per design and profile) as and where required. The rates shall include cost of all materials, labour, T& P, wastage, transportation etc. required for proper completion of work. It shall be made out of following profile.-Bank's logo (300mm dia. / 300mm x 300mm).All complete to the satisfaction of the Architect.				
8.5	VERTICAL BLINDS	Sq.Ft	36.00		
	Providing & fixing in position vertical blinds of Vista as per approved colour by Bank's Engineer & Architect.				
8.6	WOOD PLANTER WITH PLANTS				
	Providing and placing in position planter made of phenol bonded 19 mm thick Premium Board (Century & Green) with top front and sides finished in 1.0 MM Thick laminate including GI trough with sand and marble chips filling and artificial plants as per the approval of the architect of not less than Rs.750. The design of the grooves shall be as per detailed drawing and complete as per Architects direction	No.	5.00		
8.7	POSTER FRAMES -WALL MOUNTED	No.	2.00		
	2 sheets of 36" x 24" clear acrylic (poster to be sandwiched in between). Outer sheet is 5mm thick and bevelled crystal edge polished for 3/4" at 8-10 degrees on all sides in the front.Rear sheet is 5 mm thick flat.				
8.8	PAINTING & FINISHING WORK				
8.8.1	Painting on Walls and Ceilings with two or more coats of first quality of Acrylic Emulsion (Make & Shade Approved by Bank / Architect). It shall include for preparing the surfaces clean, even and smooth with thoroughly brushing with broom, scratching with patti and sand papering respectively, so that the surfaces are free from oil, grease, dirt, mortar droppings & other foreign and loose matter. It shall also include for preparing the surface and filling of holes with 2 coat of first quality acrylic wall putty (Birla Wall Care / JK / Asian) before priming coat of whiting / approved primer. The rate shall include cost of all materials such as plaster of paris, whiting /primer, glue (Fevicol), indigo / stainer, brushes, sand paper, patti, dhoti, broom stick, clean water with storage and other containers, labour, scaffolding / ladder charges, cleaning of floors and other sundries etc., all complete to the satisfaction of the Architect. Please note that in	Sq.Ft	3000.00		

	the Branch Hall, walls are to be painted below false ceiling and ceiling is not be painted.				
8.8.2	Providing & applying 2 coats of first quality synthetic enamel paint over a coat of Zinc Chromate metal primer to steel surfaces (window grill, collapsible gate) all of approve make and shade including surface preparation by complete scrapping the existing paint / rust on grills / shutter by using chemical paint striper or suitable approved method, cleaning, filling holes, smoothening the surface all complete as directed by Bank's Engineer. (Measurement Coefficient for each side = 0.5)	Sq.Ft	110.00		
8.8.3	Rolling Shutter as same as above in 8.8.2 but measurement shall be taken for each side with coefficient 1.10 each side.	Sq.Ft	400.00		
A	TOTAL AMOUNT				
B	GST AMOUNT (..... %)				
C	GROSS AMOUNT INCLUSIVE OF GST (A+B)				

GROSS AMOUNT IN WORDS :

Rupees..... only

Place:
Date:

Signature & Seal of the Tenderer