

INDIAN BANK Zonal Office Berhampur (Odisha)

Plot No.704/7172 & 704/7174 1st Floor Sri Krishna Vihar Chowk Main road, Ambapua Berhampur – 760011, Odisha Phone: 0680-2404016

Email: zoberhampur@indianbank.co.in

INVITATION OF TENDER

RATE CONTRACT FOR NEW INSTALLATION, REPAIR AND MAINTENANCE
OF FIRE ALARM SYSTEM, BURGLAR ALARM SYSTEM, CCTV AND FIRE EXTINGUISHERS
(INCLUDING AUTO DIALERS)
FOR THE INDIAN BANK OFFICES/BRANCHES INCLUDING ATM SITES
UNDER BERHAMPUR ZONE

Tender Documents Availability : 14th March 2023

Last Date of Tender Submission : 13:00 PM on 28th March 2023

Date of Technical Bid Opening : 15:30 PM on 28th March 2023

EMD: by way of a demand draft for Rs. 5,000/- (Rupees Five Thousand only) favouring

Indian Bank Zonal Office, Berhampur and payable at Ambapua Branch.

TABLE OF CONTENTS

SI. No.	Content	Page
1.	Schedule of Events and Important Definitions	<u>No</u> 3
2.	Introduction and Eligibility Criteria	4
3.	Nature and Scope of Work, Application Form, Rate Contract Process	5
4.	Performance and Product Certification	6
5.	Payment Terms and Terms & Conditions of Contract	7
6.	Conditions for Application Rejection/ Cancellation	8
7.	Monitoring of Performance & other Conditions	8
8.	EMD Amount, Jurisdiction and Governing Law	8
9.	Liquidated Damages, Validity Period	9
10.	Bank's Discretion, Evaluation Criteria	9
11.	Patent Rights, Termination for Insolvency, Liability	10
12.	Warranty, Deliverables and Timelines, Specification	11
13.	Dispute Management, Nuisance	12
14.	No Commitment to accept lowest or any TENDER, Force Majeure	12
15.	Execution of SLA	12
16.	Restriction for further Contracts , Amendments to Contract	13
17.	Confidentiality of Contract Documents & Information, Publicity	13
18.	Authorized Signatory	13
19.	Annexure - I (Application for participation in TENDER)	14
20.	Annexure - II (Bidders Profile)	15
21.	Annexure - III (List of Enclosures for Technical Bid)	17
22.	Annexure - IV (Financial Bid)	18

SCHEDULE OF EVENTS

Tender Bid Document Availability	Bidding document can be downloaded from website www.indianbank.in from 14th Mar'23	
Last date and time of submission of Bids	28 th Mar'23- 13:00 PM	
Opening of Technical Bids	28 th Mar'23- 15:30 PM	
	Bidders may depute authorized	
	representatives during the opening of	
	Technical Bids. However Technical Bids would	
	be opened even in the absence of any or all	
	of the Bidders representatives.	
Contact Official and Mobile No.	Tapas Mishra, Asst. Manager (Security), Phone: 7978799729	
Address for communication and submission	Zonal Office, Plot No.704/7172 & 704/7174	
of bid	1 st Floor Sri Krishna Vihar Chowk,Main Road	
	Ambapua, Berhampur, Odisha-760011	
All correspondence relating to this Tender	zoberhampur@indianbank.co.in	
should be sent to email id		
Cost of the Tender Bid document	FREE OF COST	
Earnest Money Deposit	Rs. 5,000/- (Rupees Five Thousand only) by	
	way of a demand draft favoring Indian Bank and payable at Berhampur	

IMPORTANT DEFINITIONS

TERMS	DEFINITIONS
Bank	Indian Bank
ZO	Zonal Office, Plot No.704/7172 & 704/7174
	1st Floor Sri Krishna Vihar Chowk, Main Road Ambapua, Berhampur, Odisha-760011
Branch	Indian Bank branch (including ATM site, if available)
Off Site	ATMs Premises located separately apart from Branch ATMs
ATM	
TENDER	Request for Quotation/ Tender
Vendor	Participating Company/ Firm/ Manufacturer/ Authorized dealer
OEM	Original Equipment Manufacturer
Tender	Tender, Bid documents
Bidder	A Firm/Company/OEM/Authorized dealer participating in TENDER
FAS	Fire Alarm System
BAS	Burglar Alarm System
NA	Not Applicable

NOTICE INVITING TENDER

Rate contract for new installation, repair and maintenance of Fire Alarm, Burglar Alarm and CCTV (Including maintenance of existing Fire Alarm System, Burglar Alarm System and CCTV)

INTRODUCTION

- 1. Indian Bank, Zonal Office Berhampur, invites sealed quotations in two bid system for rate contract for new installation, repair and maintenance of Fire Alarm, Burglar Alarm & CCTV Systems (including maintenance of existing Fire Alarm System, Burglar Alarm System and CCTV) at Branches, Offices and Off Site ATMs under its jurisdiction comprising of 09 districts of **Odisha** i.e. Ganjam, Gajapati, Koraput, Kandhamal, Kalahandi, Malkangiri Nayagarh, Nabarangpur and Rayagada Annexure-V) (list enclosed in and category of branches from reputed Firms/Manufacturers/Authorized dealers. The first bid shall be Technical Bid and the sealed envelope of Technical Bid shall contain the details of OEM, Acceptance of terms and conditions, and other eligibility conditions, etc. The second bid shall be **Financial Bid** and the sealed envelope of Financial Bid shall contain the price information of the product and services in prescribed format as per the annexure. Financial bids shall invariably be submitted in sealed envelope. Any financial bid found open for any reason shall make the bidder ineligible for participation.
- 2. India Bank, Zonal Office Berhampur has a network of 41 Branches, 2 Offices and ATMs spread across above districts of Odisha. The branches, offices and Off Site ATMs function directly under the Zonal office.

ELIGIBILITY CRITERIA

- 3. The eligibility criteria for rate contract are given below and only those agencies that fulfill the following criteria are eligible to bid.
 - a) The prospective bidder should be a registered company/ firm including manufacturers (OEMs as described in point no.7) or their authorized dealers, capable of providing Fire Alarm System, Burglar Alarm System and CCTV for New installation, repair and maintenance of Fire Alarm System, Burglar Alarm System and CCTV (including maintenance of existing Fire Alarm System, Burglar Alarm System and CCTV) and should be in business for at least **3 years**.
 - b) The OEM/ its authorized dealers must have his own registered office with adequate technical manpower and material in Odisha so as to attend calls from the Branches easily in the Districts of Ganjam, Gajapati, Koraput, Kandhamal, Kalahandi, Malkangiri, Nayagarh, Nabarangpur and Rayagada. Proof for the same to be submitted like Lease Agreement/ Registration Certificate under Shops and Establishment Act. The Bank may inspect the facilities of the Manufacturer/ Firm/ Company/ Dealer/ Vendor to verify the genuineness and to ensure the conformity with the details given. (Details to be provided in format Annexure II).
 - c) There is no minimum limit to annual turnover. However, the prospective applicant/bidder should be in profit for last three years. (Relevant copies of Balance Sheets Seal & Signature of Vendor

and IT return to be submitted).

- d) The prospective applicant/ bidder must be on panel of at least one PSUs / Banks (Public/Private)/NBFCs/Government Departments and have at least one running contract with PSU/ Banks (Public)/NBFCs/Government Department. Performance report/ certificate of running contract for same to be enclosed.
- e) The bidders should have valid PAN, GST registration number etc., allotted by competent authorities and to provide latest GST Returns filed.
- f) The prospective applicant/bidder should have requisite trade/manufacturing/factory license from appropriate authority (BIS).
- g) The Company/ Firms/ Authorized dealer which participates in the Tender process shall only be eligible for rate contract. **All existing empanelled vendors have to apply afresh.** Telephonic/ email intimation to prospective applicants for participating in **TENDER** will not be initiated from ZO, even to the existing vendors.

NATURE AND SCOPE OF WORK

- 4. New installation, repair and maintenance of CCTV, FAS and BAS (including maintenance of existing CCTV, FAS and BAS) at branches, offices and Off Site ATMs of Indian Bank, Berhampur Zone. Concerned Vendor will have to enter into an agreement (as per the format decided by the bank) with the Zone and shall start the work from the date of issuance of the work order. The work order for new installation, repair and maintenance of CCTV, FAS and BAS (including maintenance of existing CCTV, FAS and BAS) shall be placed by the Zone as per requirement basis.
 - a) Please note that the invitation of tender is for new installation, repair and maintenance of CCTV, FAS and BAS (including maintenance of existing CCTV, FAS and BAS) installed in all existing Branches & offices of the Zone. However, new installations are subject to requirement of Bank. Bank has discretion to revise the scope of work upward / downward as per its requirement.
 - b) It is to bring to the notice of prospective Applicants that they will be required to supply and replace newly installed components at their own cost during warranty period and the warranty period of each component has to be specified in the tender document.
 - c) The Vendor will maintain the data sheet of Fire Alarm System, Burglar Alarm System and CCTV of each branch, Office and Off Site ATMs with details, such as manufacturing date, date of installation, warranty valid up to, AMC carried out on, AMC due on, etc. A copy of the Branch / Office wise data sheet of CCTV, FAS and BAS (including maintenance of existing CCTV, FAS and BAS) to be provided to the Zonal Office as well as to the concerned Branch/office.
 - d) The Vendor must ensure quarterly AMC visit. **There should be a gap of minimum 45 days** between two AMC visits. During AMC Visit all preventive maintenance activities to be carried out and recorded.
 - e) The vendor will follow the norms and procedures laid down for installation, repair and maintenance of CCTV, FAS and BAS (including maintenance of existing CCTV, FAS and BAS).
 - f) The vendor will carry defective components to his own workshop for repair only after taking written prior approval of the Branch Manager.
 - g) The detail specification for new installation will be decided by the Zonal Office.
 - h) The vendor will impart training to staff members about operating procedure, Seal & Signature of Vendor

system testing & tuning, playback, data retrieve, etc during the AMC visit.

APPLICATION FORM

- 5. The application form to be filled and submitted as per Annexure I (Cover Letter) and Annexure II (Bidder Profile). The tender notice should be signed by authorized signatory on each page with official seal and enclosed along with the Application Documents **RATE CONTRACT PROCESS.**
- 6. The selection of Bidders for supply, new installation, repair and maintenance of CCTV, FAS and BAS (including maintenance of existing CCTV, FAS and BAS) shall be done in two bid format as under.

a) PHASE I -TECHNICAL BID:

- i) Technical bid shall be submitted in a separate sealed envelope. It should be super scribed in bold "Technical Bid for New installation, repair and maintenance of CCTV, FAS and BAS (including maintenance of existing CCTV, FAS and BAS)".
- ii) Technical bid shall contain Annexure I (Application), Annexure II (Bidder profile) and Annexure III (Testimonials).
- iii) The Applications of the bidders (Annexure II) will be valid for 120 days from the date of opening of the same.
- iv) The selection/ short listing of the applications so received will be done by carrying out evaluation and checking of various parameters/ criteria fixed by the bank.
- v) The technical bids shall be opened at **15:30 PM on 28th March 2023**, or on any suitable date as decided by the bank's committee for the purpose. If any change in the date will be published in this website.
- vi) An undertaking that firm is capable of undertaking installation, repair and maintenance of CCTV, FAS and BAS (including maintenance of existing CCTV, FAS and BAS) work in rural and far away areas where majority of bank's branches are located (To be enclosed with Technical Bids).

b) PHASE II - FINANCIAL BID

- i) Financial bid shall be submitted in a separate sealed envelope. It should be super scribed in bold "Financial Bid for New installation, repair and maintenance of CCTV, FAS and BAS (including maintenance of existing CCTV, FAS and BAS)".
- ii) Financial bids of only technically qualified short listed bidders will be opened. Bank's evaluation of the financial bids will take into account the status of compliance of terms and conditions.
- iii) The Financial Bid should contain all relevant rates and charges (Service Charge / Installation Charge), taxes and the rates should be quoted in Indian Rupees only. GST component must be explained (inclusive/exclusive) clearly. In case of any ambiguity during comparing quoted prices arises because of GST, Bank may take a call to disqualify such bids.
- iv) The Bank may select multiple vendors for entering into rate contract and becoming L1 is not the only criteria.

Seal & Signature of Vendor

c) Interested Bidders may arrange to submit their application duly complete in all respects in a sealed envelope cover superscripted "Application for New Installation, repair and maintenance of CCTV, FAS and BAS (including maintenance of existing CCTV, FAS and BAS) " and this envelope should contain two separate envelopes superscripted as details below:

Envelope 1 : Technical Bid Envelope 2 : Financial Bid

And, it should reach on or before **13.00 PM on 28th March 2023**, at the following address: Zonal Office, Plot No.704/7172 & 704/7174,1st Floor Sri Krishna Vihar Chowk,Main Road Ambapua, Berhampur, Odisha-760011

PERFORMANCE AND PRODUCT CERTIFICATION:

- 7. The Bidders should have the following product certification and other criteria: -
- a) **Product Certification:** The products of the Bidder must have certification of quality given by the Bureau of Indian Standard (BIS) and acceptable to Bank. The products should be based on latest technology for the specific requirement.
- b) **OEM Certificate:** The Bidder should have OEM certificate along with confirmation that they would supply spare parts for the quoted components for a period of 5 years from the date of installation.
 - i) OEM should be ISO 9001 certified.
 - ii) Documents of Manufacturing license/ Registration of the OEM factory need to be submitted for verification.
 - iii) Product Certification copies to be attached as per the BIS specifications.
 - v) The firm should produce authorization from OEM for its offered makes in original.
 - vi) Multiple brand Techno-commercial bids from single bidder will be rejected.
 - vii) Serial number & IS certificate of products to be provided by the OEM.
 - viii) Audit for Banks, whether actual material is provided or not, needs to be done by OEM as and when required by Bank without any additional cost.
- c) Past Record: The Bidder or their entities should not have been blacklisted by any PSU/PSB/Government Organization in past 3 years and undertaking in this regard to be submitted.
 - i) Bidders A/c should not be classified as **NPA** by any bank. A self- declaration in this regards to be submitted by bidder along with Bid Documents.

PAYMENT TERMS

- 8. No advance payment shall be made against purchase order
 - i) Payments shall be made after delivery & installation of new CCTV/FAS/BAS at per site Basis. The payment shall be made against delivery challans and invoices and commissioning report duly signed by the Branch Manager.
 - ii) The vendor empanelled to have a Bank Account with Indian Bank for operational convenience.
 - iii) The Annual Maintenance Charges shall be paid once in **three months** subject to Seal & Signature of Vendor

satisfactory maintenance for the previous three months. Vendors failing to render requisite maintenance service visits shall be paid only on the pro rata Basis for the number of mandatory service visits.

- iv) All Annual Maintenance Charges shall be paid from Zonal Office only.
- iii) All other terms and conditions are spelt out in the Terms and conditions attached to this tender.

TERMS & CONDITIONS OF CONTRACT (TCC)

- 9. Indian Bank's Right to Accept/ Reject any/or all Application:
 - i) Indian Bank reserves the right to accept/ reject any or all application and to annul the rate contract process and accept/ reject all applications at any time prior to TENDER process or any time after TENDER process, without thereby incurring any liability to the affected Bidders or any obligation to inform the affected Bidders of the grounds for Indian Bank action.
 - ii) Indian Bank's Right to Split the Service Area Work: Indian Bank reserves the right to split and distribute the work among the participating Bidders partly or fully amongst the bidders agreeing at lowest quoted rates. Indian bank reserves the Right to Issue Clarifications, Addendums, and Corrigendum etc.
 - iii) Discrepancies or omission, if found by any bidder, in the terms & conditions of the tender document, or if any clarification is sought by the bidder, a written request, to the application inviting authority, for correction / clarification or interpretation can be submitted up to **5.00PM**, **26th March 2023 at <u>zoberhampur@indianbank.co.in</u>. Indian Bank can at any time issue clarifications, addendums or corrigendum. The same will be published in the bank's website. The Bidders are advised to regularly visit the Bank's website.**

CONDITIONS FOR APPLICATION REJECTION/ CANCELLATION:

- 10. Bidder's application for rate contract or the registration after rate contract of Bidder may be rejected / cancelled on the following grounds:
 - i) Any effort by Bidder/applicant to influence Indian Bank's decisions on evaluation and registration process may result in rejection of application or cancellation of registration.
 - ii) Conditional applications will not be considered and will be rejected summarily.
 - iii) Submission of false/fake Application Documents or if the information provided by the Bidder is found to be incorrect/misleading at any stage / time during the rate contract process or thereafter.
 - iii) Applications received by Indian Bank after the last date and time prescribed for receipt of application or applications without signature of person(s) duly authorized on required pages of the application or applications without power of authorization and any other document consisting of adequate proof of the ability of the signatory to bind the Bidder shall be rejected.
 - iv) Malpractice / attempt to influence / Manipulation of rates at Zonal level by itself or by cartelization shall be viewed very seriously. If such a situation comes to the notice and/ or there are reasons/ circumstances for Indian Bank to believe so, the concerned Bidder

Seal & Signature of Vendor

will be called in to give justification of rates quoted by them to the Zonal Office. If they are not able to give a proper/ satisfactory justification of their quoted rates, their rate contract / enlistments are liable to be cancelled.

- v) If the Bidders are found, subsequent to their registration, not complying with, any of the eligibility criteria.
- vi) If the performance and services of the bidder have been found poor or sub-standard.
- vii) If it is found that false/amplified/manipulated bill(s) raised by vendor.
- vii) Any other grounds as decided by Indian Bank management after due diligence.

MONITORING OF PERFORMANCE AND OTHER CONDITIONS:

- 11. The Bidder's performance on the job will be constantly monitored for quality, adherence to the Safety Regulations, Labour / Statutory regulations, Conduct / Discipline etc, while executing jobs. Any deviations from stated conditions can lead to appropriate deterrent action as deemed fit by Indian Bank.
 - i) Indian Bank reserves the exclusive right and absolute discretion to call for tenders for any job or otherwise as deemed fit from open market, even during the validity of the rate contract period.
 - ii) Successful rate contract by Indian Bank is no guarantee of any future award of work or inclusion on a particular tender list.

EMD AMOUNT:

12. Rs. 5,000/- (Rupees Five Thousand only) by way of a demand draft favouring **Indian Bank, Zonal Office, Berhampur** and payable at **Ambapua branch**.

JURISDICTION AND GOVERNING LAW:

13. All disputes or differences whatsoever arising between the parties out of or in relation to the construction/ meaning and operation or effect of this rate contract document or breach thereof shall be settled amicably. If, however, the parties are not able to solve it amicably the same shall be settled by arbitration in accordance with the Arbitration and Conciliation Act 1996 (with latest amendments) and the award made in pursuance thereof shall be binding on the parties. The Arbitrator/Arbitrators shall give a reasoned award. Any appeal will be subject to exclusive jurisdiction of courts at Berhampur.

LIQUIDATED DAMAGES:

14. Any delay in completion of the work over the stipulated period will attract penalty of 0.5% of the contract value (site Basis) per week subject to maximum of 10% of the contract value. The Bank reserves its right to recover this amount by any mode, which includes adjusting from any payment to be made by the Bank to the Vendor.

VALIDITY PERIOD:

- 15. The successful Bidders/ Firms/ Vendors will remain in the list of the Bank for **three years** from the date of contract or till the completion of next contract period at the Bank's own discretion (whichever is earlier).
 - i) The Rate contract will be valid for **(03) Three Year. Initially work will be allotted to one year (1) and will be renewed on yearly basis up to maximum three years.** On successful completion of first year, renewal for second year will be subject to the satisfactory performance and review by Security Department. Revision of rates during the contract period will not be entertained by Bank for whatsoever reasons.
 - ii) Contract will be valid only, if all eligibility criteria mentioned in the Tender Notice are fulfilled during the entire contract period.
 - iii) If the service provided by bidder is found to be poor and unsatisfactory or if at any point of time during the Tender process it is found that the information provided by bidder is false, the Bank reserves the right to cancel the contract. Bank's decision in this regard will be final.

BANK'S DISCRETION:

- 16) Bank reserves the right to reject an offer under any of the following circumstances:
 - i) Incomplete offer and/or all documents not attached.
 - ii) Offer is not in conformity with the terms and conditions stipulated in this document.
 - iii) Specifications stipulated in TENDER are not met with.
 - iv) If Financial Bid and Technical Bid are not submitted in sealed envelope separately.
 - v) Financial Bid format differs from actual Financial Bid format of Annexure IV.
 - vi) Violates any terms and conditions in the TENDER document.
 - vii) If found that the information provided in the offer is false.

EVALUATION CRITERIA

17. Technical Bids:

- i) The Technical Bid should be complete in all respects and contain all information asked for in this document. It should not contain any price information.
- ii) The Technical Bid must be submitted in an organized, numbered and structured manner (spiral binding will be appreciated). No brochures/ leaflets etc should be submitted in loose form.
- iii) Technical bid should contain all testimonials as mentioned in previous section of this TENDER document.
- iv) Bank will evaluate the technical bid considering the technical and functional parameters of bidder and evaluation matrix decided by bank.

18. Commercial Bids:

i) Commercial bids of only technically qualified short listed bidders will be opened.

Seal & Signature of Vendor

Bank's evaluation of the commercial bids will take into account the status of compliance of terms and conditions. The Price Bid should contain all relevant rates and charges (Service charge / installation Charge) and the rates should be quoted in Indian Rupees only.

- ii) Cost economics of the tender will be decided on the Basis of Total Cost of Equipment/cost of components having low MTBF/ services as enumerated in Annexure-IV.
- iii) Rates of equipment/services will be arrived individually based on commercial bids received and the contract will be awarded accordingly.

PATENTS RIGHTS

- 19. The Vendor shall indemnify the purchaser against all third party claims on infringement of patent, trademark or industrial design rights arising from use of the Goods, or any part thereof in India.
 - i) The vendor shall, at their own expense, defend and indemnify the Bank against all third party claims of infringement of intellectual Property Right, including Patent, trademark, copyright, trade secret or any part thereof in India or abroad.
 - ii) The Vendor shall expeditiously extinguish any such claims and shall have full rights to defend it there from. If the Bank is required to pay compensation to a third party resulting from such infringement, the Vendor shall be fully responsible for, including all expenses and court and legal fees.
 - iii) The Bank will give notice to the Vendor of any such claim without delay, provide reasonable assistance to the Vendor in disposing of the claim, and shall at no time admit to any liability for or express any Intent to settle the claim.
 - iv) The Vendor shall grant to the Bank a fully paid-up, irrevocable, non- exclusive license throughout the territory of India or abroad to access, replicate and use software (and other software items) if any, provided by the Vendor, including-all inventions, designs and marks embodied therein in perpetuity.

TERMINATION FOR INSOLVENCY

20. The Bank may at any time terminate the Contract by giving written notice to the Bidder, if the Bidder becomes bankrupt or otherwise insolvent. In this event, termination will be without compensation to the Bidder.

LIABILITY

- 21. Bidder's aggregate liability under the contract shall apply to third party claims for bodily injury/ electric shock (including death) and damage to real property (due to malfunction of equipment) and tangible personal property caused by bidder's gross negligence/ lapse or due to below standard equipment used by Bidder.
 - i) The Bidder shall be liable for any indirect, consequential, or special damages due to malfunction of the security equipments under the agreement / purchase order.

WARRANTY

- 22. The offer must include on-site warranty of at least one year or as offered by the OEM but not less than one year from the date of installation and replacement of components however there should not be any additional cost for the warranty period.
 - ii) Vendor shall be fully responsible for the manufacturer's warranty in respect of proper design, quality and workmanship of all equipment, accessories, etc., covered by the offer.
 - iii) The Vendor must warrant all equipment, accessories, spare parts etc, against any manufacturing defects during the warranty period.
 - iv) During the warranty period the Vendor shall maintain the equipment and repair / replace all the defective components at the installed site at no additional charge of whatsoever nature to the Bank.

DELIVERABLES & TIMELINES

23. The Vendor should ensure that the defects reported in the CCTV, FAS and BAS or its components, software, etc supplied to the Bank on any working day is set right within one day. The defect will be reported by the office/branch directly to vendor, may be in the form of oral, telephone, notice, email, or any other mean of communication. The vendor shall generate a complaint number for tracking the complaint status. In case, the system or any equipment cannot be repaired within the stipulated period, the Vendor should provide a replacement till the system/ equipment is returned duly repaired.

SPECIFICATION

24. The detailed technical description is enumerated below. The specifications given are as per minimum requirement. Vendors can quote equivalent or higher technical specifications to meet the Bank's requirements. However, no weightage would be given for higher configurations. All components should be BIS certified.

TECHNICAL SPECIFICATIONS

Note:

- (i) Firms should state "**Yes**" if the Security Equipment offered by them conform to the required specifications, or else they should state "**No**". The selected firms who qualifies Stage-III of the evaluation Process will be required to demonstrate these specifications in the Stage-IV.
- (ii) Bids will be rejected if the firm fails to fulfill the minimum technical requirement as given below.
- (iii) If technical specification given anywhere in this document contradicts the under mentioned specification then higher specification whichever is, will prevail.
- (iv) Technical Specification undertaking placed at Annexure VII "APPENDIX B" to be filled up by all firms.
- (v) The firm must give a full demonstration at Zonal office, Berhampur at their own cost. In case of system provided during demonstration is of higher specification than the prescribed specification of the Bank. The higher specification will be finalized in the same rate

CONVENTIONAL TYPE FIRE DETECTION AND ALARM SYSTEM

(A) CONTROL PANEL SPECIFICATIONS

SI.	Technical Specification	Compliance Status Yes/No)
i)	2 / 4 zone Main Control Panel & repeater control panel should be latest microprocessor technology based and as per IS: 2189-2008.	
ii)	The panel should be compatible with all type of standard conventional detectors.	
iii)	The Panel should have a manual OFF switch for manual operation in case of continuous fault alarm. The Panel should have 2 or 4 zones or more and Zone disable switches accordingly to the number of zones.	
iv)	On activation it should initiate Audio alarm (The sound characteristic of the alarm should be continuous and similar throughout the protected premises) as well as visual signal on sector/zonal panel of the control panel.	
v)	The Size of the control panel is normally referred by number of zones. Each zone can be connected with the conventional detectors not exceeding 10.	
vi)	The Panel should be have inbuilt with SMPS with spike/Transient reduction circuit, to avoid any false alarming in case of transient/abrupt voltage fluctuations.	
vii)	The Panel should have Test Certificate with details like Model No., Serial. No. Zones, etc.	
viii)	The Brouchers for the Panel shall be submitted. The Panel should have <i>approvals</i> / listing of BIS / UL /LPCB / FM / VDS.	
ix)	The Panel should have feature of continuous uninterrupted power supply in case of External Power supply failures. The battery backup with built in battery charger for not less than 10-12 hours normal working.	

(B) **SMOKE DETECTORS AND SPACING**

The System should have smoke detectors of both ionization type (below false ceiling) and optical type (above false ceiling) conforming to the IS: 2189- 2008 & IS: 15908-2011. Both ionization and optical type smoke detectors will be installed based on the requirement of Bank. For the smoke detector, the Spacing between two detectors should be 24 feet and spacing from the boundary wall or cabin wall should be not more than 12 feet. Every cabin / enclosed area likes UPS Room, Electrical Distribution Room etc should have a separate smoke detector. The detector should have LED, which should flash periodically to indicate that the detector is in proper working mode and glow continuously if smoke is detected. After designing the detector spacing, it shall be cross-checked to ensure that there is at least one smoke detector for every 100 m2 of the compartment area. At the time of installation and prior to commissioning, every detector should be allotted an identification number. All the detectors inside	Compliance Status (Yes/No)
to the IS: 2189- 2008 & IS: 15908-2011. Both ionization and optical type smoke detectors will be installed based on the requirement of Bank. For the smoke detector, the Spacing between two detectors should be 24 feet and spacing from the boundary wall or cabin wall should be not more than 12 feet. Every cabin / enclosed area likes UPS Room, Electrical Distribution Room etc should have a separate smoke detector. The detector should have LED, which should flash periodically to indicate that the detector is in proper working mode and glow continuously if smoke is detected. After designing the detector spacing, it shall be cross-checked to ensure that there is at least one smoke detector for every 100 m2 of the compartment area. At the time of installation and prior to commissioning, every detector should be allotted an identification number. All the detectors inside	
type smoke detectors will be installed based on the requirement of Bank. For the smoke detector, the Spacing between two detectors should be 24 feet and spacing from the boundary wall or cabin wall should be not more than 12 feet. Every cabin / enclosed area likes UPS Room, Electrical Distribution Room etc should have a separate smoke detector. The detector should have LED, which should flash periodically to indicate that the detector is in proper working mode and glow continuously if smoke is detected. After designing the detector spacing, it shall be cross-checked to ensure that there is at least one smoke detector for every 100 m2 of the compartment area. At the time of installation and prior to commissioning, every detector should be allotted an identification number. All the detectors inside	
Bank. For the smoke detector, the Spacing between two detectors should be 24 feet and spacing from the boundary wall or cabin wall should be not more than 12 feet. Every cabin / enclosed area likes UPS Room, Electrical Distribution Room etc should have a separate smoke detector. The detector should have LED, which should flash periodically to indicate that the detector is in proper working mode and glow continuously if smoke is detected. After designing the detector spacing, it shall be cross-checked to ensure that there is at least one smoke detector for every 100 m2 of the compartment area. At the time of installation and prior to commissioning, every detector should be allotted an identification number. All the detectors inside	
For the smoke detector, the Spacing between two detectors should be 24 feet and spacing from the boundary wall or cabin wall should be not more than 12 feet. Every cabin / enclosed area likes UPS Room, Electrical Distribution Room etc should have a separate smoke detector. The detector should have LED, which should flash periodically to indicate that the detector is in proper working mode and glow continuously if smoke is detected. After designing the detector spacing, it shall be cross-checked to ensure that there is at least one smoke detector for every 100 m2 of the compartment area. At the time of installation and prior to commissioning, every detector should be allotted an identification number. All the detectors inside	
 24 feet and spacing from the boundary wall or cabin wall should be not more than 12 feet. Every cabin / enclosed area likes UPS Room, Electrical Distribution Room etc should have a separate smoke detector. The detector should have LED, which should flash periodically to indicate that the detector is in proper working mode and glow continuously if smoke is detected. After designing the detector spacing, it shall be cross-checked to ensure that there is at least one smoke detector for every 100 m2 of the compartment area. At the time of installation and prior to commissioning, every detector should be allotted an identification number. All the detectors inside 	
 ii) not more than 12 feet. Every cabin / enclosed area likes UPS Room, Electrical Distribution Room etc should have a separate smoke detector. The detector should have LED, which should flash periodically to indicate that the detector is in proper working mode and glow continuously if smoke is detected. After designing the detector spacing, it shall be cross-checked to ensure that there is at least one smoke detector for every 100 m2 of the compartment area. At the time of installation and prior to commissioning, every detector should be allotted an identification number. All the detectors inside 	
Electrical Distribution Room etc should have a separate smoke detector. The detector should have LED, which should flash periodically to indicate that the detector is in proper working mode and glow continuously if smoke is detected. After designing the detector spacing, it shall be cross-checked to ensure that there is at least one smoke detector for every 100 m2 of the compartment area. At the time of installation and prior to commissioning, every detector should be allotted an identification number. All the detectors inside	
detector. The detector should have LED, which should flash periodically to indicate that the detector is in proper working mode and glow continuously if smoke is detected. After designing the detector spacing, it shall be cross-checked to ensure that there is at least one smoke detector for every 100 m2 of the compartment area. At the time of installation and prior to commissioning, every detector should be allotted an identification number. All the detectors inside	
The detector should have LED, which should flash periodically to indicate that the detector is in proper working mode and glow continuously if smoke is detected. After designing the detector spacing, it shall be cross-checked to ensure that there is at least one smoke detector for every 100 m2 of the compartment area. At the time of installation and prior to commissioning, every detector should be allotted an identification number. All the detectors inside	
 iii) indicate that the detector is in proper working mode and glow continuously if smoke is detected. After designing the detector spacing, it shall be cross-checked to ensure that there is at least one smoke detector for every 100 m2 of the compartment area. At the time of installation and prior to commissioning, every detector should be allotted an identification number. All the detectors inside 	
continuously if smoke is detected. After designing the detector spacing, it shall be cross-checked to ensure that there is at least one smoke detector for every 100 m2 of the compartment area. At the time of installation and prior to commissioning, every detector should be allotted an identification number. All the detectors inside	
After designing the detector spacing, it shall be cross-checked to ensure that there is at least one smoke detector for every 100 m2 of the compartment area. At the time of installation and prior to commissioning, every detector should be allotted an identification number. All the detectors inside	
ensure that there is at least one smoke detector for every 100 m2 of the compartment area. At the time of installation and prior to commissioning, every detector should be allotted an identification number. All the detectors inside	
compartment area. At the time of installation and prior to commissioning, every detector should be allotted an identification number. All the detectors inside	
At the time of installation and prior to commissioning, every detector should be allotted an identification number. All the detectors inside	
v) should be allotted an identification number. All the detectors inside	
• • • • • • • • • • • • • • • • • • •	
rooms /cabins and above false ceiling or generally hidden should	
have external response indicators (R.I.) sited at prominent place.	
vi) The detectors should have approvals / listing of BIS / UL /LPCB / FM / VDS.	

C. HEAT DETECTORS AND SPACING

SI.	Technical Specification	Compliance Status (Yes/No)
i)	For the heat detector, Spacing between two heat detectors should be 17 feet conforming to the IS: 2189-2008 & IS 15908-2011. These detectors should be installed in Cooking Kitchen, Pantry etc.	
ii)	After designing the detector spacing, it shall be cross-checked to ensure that there is at least one heat detector for every 50 m2 of the Compartment area.	
iii)	The detector should have LED, which should flash periodically to indicate that the detector is in proper working mode and glow continuously if heat is detected.	

	At the time of installation and prior to commissioning, every detector	
iv)	should be allotted an identification number. All the detectors inside	
,	rooms / cabins and above false ceiling or generally hidden should	
	have external response indicators (R. I.) sited at prominent place.	
V)	The detectors should have approvals / listing of BIS / UL /LPCB / FM	
	/ VOS.	

D. UV / IR FLAME DETECTORS AND SPACING

SI.	Technical Specification	Compliance Status (Yes/No)
i)	The detector can be installed in UPS Room, Electrical Distribution Room and Storage Area etc where chances of fire are higher. This detector should be installed to conforming IS: 2189-2008 & IS 15908-2011.	
ii)	The detector should have LED, which should flash periodically to indicate that the detector is in proper working mode and glow continuously if flame is detected.	
iii)	At the time of installation and prior to commissioning, every detector should be allotted an identification number. All the detectors inside rooms / cabins and above false ceiling or generally hidden should have external response indicators (R. I.) sited at prominent place.	
iv)	The detectors should have approvals / listing of BIS / UL /LPCB / FM / VOS.	

E. <u>AUTO DIALER</u>

SI.	Technical Specification	Compliance Status (Yes/No)
i)	In built GSM/PSTN Auto-Dialer as per requirement with facility to dial at least 5 telephone / Mobile Nos. each and voice message of at least 20 seconds.	

F. OTHER ITEMS / DEVICES

SI.	Technical Specification	Compliance Status (Yes/No)
i)	All the wiring shall be by means of 2 core 1.5 sq. mm copper conductor FRLS armored and shielded copper cable.	
ii)	The Manual Call Point (MCPs) should be installed in entry & exit point of the floor. The MCPs should be break glass type with hammer or thumb press type.	
iii)	The sounders for fire alarm system should be electronic hooters/horns/electric bell having a frequency range of 500 to 1000 Hz.	

SECURITY ALARM SYSTEM

SI.	Technical Specification	Compliance Status (Yes/No)
i)	Security Alarm control panel Micro-processor based (Tamper-proof) at	
	least 4 zone (for Branches) & 2 zone (for ATMs), which raise loud	
	sound, alarm and send SMS / call alerts to branch official / police in case of activation, tampering & intrusion.	
ii)	System must have capability for Day &Night mode of operation &vice	
,	versa manually through removable key or electronic keypad.	
iii)	Compatible with 10 or more panic switches (for Branches) & 4 or	
	more panic switches (for ATMs)	
iv)	Should have night mode with provision to connect at least five	
	sensors, single or multiple type, i-e Passive infrared (PIR) sensor,	
	Magnetic sensors, Heat Sensor, Vibration sensor& Pressure Switch.	
v)	The PIR sensor should be pet immune.	
vi)	Should have programmable time delay of alarm activation in day mode and immediate activation in night mode.	
vii)	2 Hooter (the sound of alarm should be clearly audible up to 500	
	meters) and one in built hooter.	
viii)	Panel should have in built battery for backup along with battery	
	charger with over charging and deep discharging protection.	
ix)	Panel should be compatible with all types of standard sensors and panic switches available in the market.	
x)	Panel should have inbuilt/compatible for installation of auto dialer (with display).	
xi)	Should be compatible to connect additional Sensors/Panic switches.	
xii)	System should have a timer to stop the siren sound automatically after the pre-fixed time.	
xiii)	The system should work on quad linear technology to avoid any false	
	alarm activation in night mode.	
xiv)	The system should be user friendly and should be easy to operate.	
xv)	Programming menu should be user password protected for safety.	
xvi)	Test report by the Regional Electronic Test Development Centers is	
**\	mandatory for Security Alarm System.	
xvii)	CE or FCC or UL certification	

CCTV SYSTEM

1. NVR BASED CLOSE CIRCUIT TELEVISION SYSTEM

(A) NVR 8/16 CHANNEL NETWORK VIDEO RECORDER

System Parameter	Technical Specifications	Compliance Status (Yes/No)
Main Processor	Quad-core embedded processor	
Operating System	Embedded LINUX	
Display		
Interface	2 HDMI (1 HDMI up to 3840x2160, Different Source), 1 VGA	
Resolution	3840x2160, 1920x1080, 1280x1024, 1280x720, 1024x768	
Multi-screen	1 st screen: 8/16 CH: 1/4/8/9/16 2 nd screen: 1/4/8/9/16	
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording	
Video Detection and Alarm		•
Trigger Events	Recording, PTZ, Tour, Alarm Out, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips	
Video Detection	Motion Detection, MD Zones: 396 (22 x 18), Video Loss and Tampering, Scene Change Detection	
Alarm input	16 Channel (Low Level Effective)	
Alarm Output	4 Channel (NO/NC Programmable)	
Playback and Backup		
Sync Playback	1/4/9/16	
Search Mode	Time /Date, Alarm, MD and Exact Search (accurate to second)	
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File, Previous File, Next Camera, Previous Camera, Full Screen, Repeat, Shuffle, Backup Selection, Digital Zoom	
Backup Mode	USB Device/Network/Internal SATA burner / eSATA Device	
Storage		
Internal HDD	2 / 4 SATA Ports, with minimum 6 TB capacity for each HDD	
eSATA	1 e SATA port	
RAID	RAID 0, RAID 1, RAID 5	
Auxiliary Interface		
USB	Minimum 2 ports (Minimum 2 USB 3.0)	
RS232	1 Port, for PC Communication	
RS485	1 Port, for PTZ Control , keyboard	
Audio and Video	·	
IP Camera Input	8/16 Channel	
Two-way Talk	1 Channel Input, 1 Channel Output	
Recording		
Compression	H.265+ /H.265/H.264/MJPEG/MPEG4	
Resolution	12MP /8MP / 5MP / 4MP /3MP / 1080P / D1 &etc.	

Record Rate	320Mbps Incoming	

Bit Rate	16kbps-20Mbps for per channel	
Record Mode	Manual, Schedule(Regular(Continuous), MD,	
	Alarm), Stop	
Record Interval	1-120 min (default: 60 min), Pre-record: 1-30 sec,	
	Post- record: 10-300 sec	
Network		
Interface	1 RJ-45 ports (10/100/1000Mbps)	
Network Function	TCP/IP, DHCP, Cloud P2P, DNS, DONS, NTP, SADP, SMTP, NFS, FTP UpnPM , HTTPS	
Interoperability	ONVIF, PSIA, CGI Conformant	
Certifications	UL/FCC/CE and BIS approved	

B. <u>02 MEGAPIXEL IP BASED HD IR DOME CAMERA WITH FIXED LENS</u>

Parameter	Technical Specifications	Compliance Status (Yes/No)
Image Sensor	1 /2.8" 2 Megapixel progressive scan CMOS or	
F((.: B:	better	
Effective Pixels	1920(H)x1080(V)) or better	
Electronic Shutter	Auto/Manual, 1 /3(4)-1 /100000s	
Video Frame Rate	25/30 fps @ 2 Mega Pixel	
Scanning System	Progressive	
Min. Illumination	0.01Lux/F1 .4(Color); 0Lux/F1 .4(1R on)	
S/N Ratio	More than 50dB	
Min. IR Array LEDs Length	More than 50dB	
Day/Night	Auto(ICR) / Color I B/W	
Back Light Compensation & WDR	DWDR	
White Balance	Auto/ Manual	
Focal Length (Lens)	3. 6 mm Fixed lens	
Video Compression	H.265+ ,H.265,H.264,H.264H, MJPEG	
Resolution Frame Rate	2 M(1920x 1080)/01 (704x 576/704x 480)/CIF(352	
	x288/352x 240)	
	Main stream: {2 M/1080P(1 - 25/30fps)} 6: Sub stream: 01 /CIF(1 - 25/30fps)	
Bit Rate	H.265/H.264H: 40K - 8192Kbps; MJPEG: 40K- 16384Kbps	
Network Ethernet	RJ-45 (10/100Base-T)	
Protocol	TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP,	
	DNS, DONS, RTP, RTSP, RTCP, NTP, UpnP, SMTP,	
	IGMP, 802.1x, QoS, Ipv6	
Compatibility	ONVIF, PSIA, CGI	
Power Supply	DC12V, PoE (802.3af)	
Working Environment	-30° C-+60° C I Less than 95%RH (no	
Ingress Protection	condensation) IP66 or above	
Ingress Protection Certification		
Certification	UL/FCC/CE and BIS approved	

C. 02 MEGAPIXEL IP BASED HD IR VERIFOCAL LENS BULLET CAMERA

C. <u>UZ MIEGAPIXEL IP BASI</u>	Compliance	
Parameter	Technical Specifications	Status
Parameter		(Yes/No)
Image Sensor	1/2.8" progressive scan CMOS	(Tes/NO)
Min. Illumination	Color: 0.01@F1 .4, 0 Lux with IR	
Shutter Speed	Auto/Manual, 1 /3(4)-1 /100000s	
	2.8 mm to 12 mm motorize @F1 .4,	
Lens		
Day/Night	IR cut filter with auto switch	
DNR (Digital Noise Reduction)		
WDR (Wide Dynamic Range)	120 dB True WDR	
Compression Standard		
Video Compression	Main stream: H.265.H.265+	
Video Bit Rate	32 Kbps to 8 Mbps	
Dual Stream	Support	
Image		
Max. Resolution	1920 X 1080	
Main Stream Max.	50Hz: 25fps @(1920 x 1080, 1280 x 960, 1280 x 720)	
Sub-stream	50Hz: 25fps @(704 x 576, 640 x 480, 352 x 288, 320x 240)	
Image Settings	Brightness, saturation, contrast, sharpness are adjustable via web browser or client software.	
Image Settings	Support auto, scheduled	
Others	Mirror, BLC (area configurable), region of	
	interest (support 1 fixed region)	
Detections	Motion detection	
Alarms	Video tampering, network disconnected, IP address conflicted, HDD full, HOD error.	
Protocols Standard	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DONS, RTP, RTSP, RTCP, NTP, UpnP, SMTP, IGMP, 802.1X, QoS, Ipv6, ONVIF (PROFILE S, PROFILE G), PSIA, CGI, ISAPI	
General Function	One-key rest, anti-flicker, password protection, privacy mask, watermark, IP address filter	
Interface	,	
Communication Interface	1 RJ45 10M/100M self-adaptive Ethernet port	
Reset	Support	
General		
Operating Conditions	-30 ° C to 60° C, humidity: 95% or less (non- condensing)	
Power Supply	DC12V ± 25%, PoE (802.3af)	
Ingress Protection	IP 67	
IR array Range	Up to 30 Mtrs	
Certification	UL/FCC/CE and BIS approved	
Cei uncauon	orti colce and bis approved	

D. POE + SWITCH 08 CHANNEL SPECIFICATION

Seal & Signature of Vendor

Interface	8 x 10/100 Mbps PoE ports, UPLINK PORT 2 x 10/100/1000					
Port Standards 8: Functions	Ports 1 to 8 compliant with 802.3at					
E. POE + SWITCH 16 CHA	E. POE + SWITCH 16 CHANNEL SPECIFICATION					
Interface	16 x 10/100 Mbps PoE ports, UPLINK PORT 2 x 10/100/1000					
Port Standards 8: Functions	Ports 1 to 4 compliant with 802: 3at • Ports 5 to					

F. OTHER COMPONENTS OF CCTV

Parameter	Technical Specifications	Compliance Status (Yes/No)
SN. Hard Disk Drive (SATA II	Video Enterprise Series (Rated for24/7	
or III)	operation).	
Capacity	2TB, 4TB, 6TB ,8TB	
Monitor		
Screen size	32" diagonal LED	
Resolution (Min)	Minimum 1920 x 1080 Pixels - full HD	
Data Cable CAT-6		
Category	CAT-6E	
Type	Unarmored	
PVC Conduits for cabling sh	ould be ISI marked	
6 U Rack - (Wall Mount)	Power Strip: 6 Socket power supply: 1 No.	
	Equipment Mounting Tray: 1 No Mounting	
	screws &studs: 1 pack Transparent front door	
	with Lock and 2 Fans. Provision for cable	
	routing at the bottom of Rack.	
2 U Rack - (Wall Mount)	Power Strip: 6 Socket power supply: 1 No.	
	Mounting screws & studs: 1 pack Transparent	
	front door with Lock and Fans. Provision for	
	cable routing at the bottom of Rack.	

2. STANDALONE VANDAL RESISTANT CAMERA WITH INBUILT BACKUP CAPACITY

	Status (Yes/No)	
Image Sensor	1/2.8" Progressive Scan CMOS	
Minimum Illumination	Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux	
	(F2.0, AGC ON); B/W: 0.001 Lux @(F1.2, AGC ON),	
	0.0028 Lux @(F2.0, AGC ON), 0 Lux with IR	
Shutter Speed	1/3 s to 1/100,000 s	
Slow Shutter	Yes	
Auto-Iris	No	
Day and Night	IR Cut Filter	
Digital Noise Reduction	3D DNR	
Wide Dynamic Range	120 dB	
3-Axis Adjustment	Pan: 0° to 355°, tilt: 0° to 70°, rotate: 0° to 355°	

IR Range	Up to 40 m	
Wavelength	850nm	
Video Compression	Main stream: H.265/H.264	
	Sub-stream: H.265/H.264/MJPEG Third stream:	
	H.265/H.264	
	32 Kbps to 8 Mbps	
	G.711/G.722.1/G.726/MP2L2/PCM	
Audio Bit Rate (-S)	64Kbps(G.711)/16Kbps(G.722.1)/16Kbps(G.726)/32- 192Kbps(MP2L2)	

Image		
Maximum Resolution	1920 × 1080	
Image Enhancement	BLC/3D DNR/HLC	
Image Settings	Rotate mode, saturation, brightness, contrast,	
	sharpness adjustable by client software or web	
	browser	
On-board Storage	Built-in micro SD/micro SDHC/micro SDXC slot, up to	
	128 GB	
Target Cropping	No	
Day / Night Switch	Day/Night/Auto/Schedule/Triggered by alarm in (-S)	
Network Storage	Support built-in micro SD/micro SDHC/micro SDXC	
	card (128 GB), local storage and NAS (NFS, SMB/	
Alarm Trigger	CIFS), ANR Motion detection, video tampering, network	
Alarm Trigger	disconnected, IP address conflict, illegal login, HDD	
	3 3	
D	full, HDD error	
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS,	
	RTP, RTSP, RTCP, PPPOE, NTP, UPnP™, SMTP, SNMP,	
	IGMP, 802.1X, QoS, IPv6, Bonjour	
General Function	One-key reset, anti-flicker, heartbeat, mirror,	
	password protection, privacy mask, watermark, IP	
	address filter	
Firmware Version	V5.5.3	
On-board Storage	Built-in micro SD/micro SDHC/micro SDXC slot, up to	
	64 GB/ 128 GB	
Reset Button	Yes	
Frequency Range	2.4 GHz to 2.4835 GHz	
Channel Bandwidth	20/40MHz	
Wireless Range	50 m	
Env. Noise Filtering	Yes	
Protection Level	IP 67,IK10	
Certificates	CE,FCC,UL,	

FIRE EXTINGUISHERS SPECIFICATIONS

SI No.	Values	Specifications					
1.	Scope of work	Supply of portable fire extinguisher 4 Kgs-confirming to					
		IS-15683: latest revision and ISI marked complete with all					
		fittings					
2.	Extinguishing Media	MONNEX					
3.	ULC Fire rating	3A,55B					
4.	Cylinder material	Mild steel					
5.	Valve material	Plated brass					
6.	Handle/Lever material	Stainless steel					
7.	Operating pressure	70 Kgf/Cm2					
8.	Temperature range deg.C	-30 to 55 deg C					
9.	Nominal discharge time	10-20 sec					
10	Discharge Horn	Flexible PVC					
	These details are attached below at last page (please Read)						

Technical Specification Undertaking

We certify that the systems/services offered by us for tender confirms to the specifications stipulated by you with the following deviations.

	deviations cation is high			will	be	accepted	only	if	the	offered	b
1)							_				
							_				
							_				
4)							_				
Place.			:	Signa	iture	of Author	ised Si	ign	atory	,	
Date.				Name	e & I	Designatio	n & Se	eal	of th	e Comp	anv

(If left blank it will be construed that there is no deviation from the specifications given above) (Letter to the bank on the Supplier's letterhead)

DISPUTE MANAGEMENT

- 25. The provisions of this tender shall always be subject to Government Notifications, any rules/guidelines that may be in force from time to time.
 - i) All disputes or differences whatsoever arising between the parties out of or in relation to the construction, meaning and operation or effect of these Tender Documents or breach thereof shall be settled amicably. However, if the parties are not able to solve it amicably, the same shall be settled by arbitration in accordance with the provisions of "Arbitration and Conciliation Act 1996" or any statutory modifications or re-enactments thereof and the rules made there under and for the time being in force, shall apply to the arbitration proceedings.
 - ii) The arbitrator shall be appointed with the mutual consent of both the parties. However, there is a provision of appeal if either party is not satisfied with the arbitration award.
 - iii) During the arbitration proceedings the Bidder shall continue to work under the Contract unless otherwise directed in writing by the Bank or unless the matter is such that the work cannot possibly be continued until the decision of the arbitrator is obtained.

NUISANCE

26. The Bidder shall not at any time cause or permit anyone to cause any nuisance on the site or do anything which shall cause unnecessary disturbance or inconvenience to the Bank, Owners, Tenants or occupants of other properties near the site and to the customers/ public generally.

NO COMMITMENT TO ACCEPT LOWEST OR ANY TENDER

27. There are no obligations to accept the lowest or any other offer received in response to this notice and Bank is entitled to reject any or all offers without assigning any reasons whatsoever. The Bank will have right to opt for any new technology option for the Banks usage.

FORCE MAJEURE

- 28. Notwithstanding the provisions of TCC (Terms and Conditions of Contract), the Bidder shall not be liable for forfeiture of its performance security, liquidated damages, or termination for default if and to the extent that the delay in performance or other failure to perform its obligations under the Contract is the result of an event of Force Majeure.
 - a. For purposes of this clause, "Force Majeure" means an event beyond the control of the Bidder and not involving the Bidder's fault or negligence and not foreseeable. Such events may include, but are not restricted to, acts of the Bank in its sovereign capacity, wars or revolutions, fires, floods, epidemics, quarantine restrictions, and freight embargoes.
 - b. If a Force Majeure situation arises, the Bidder shall promptly notify the Bank in writing of such condition and the cause thereof. Unless otherwise directed by the Bank in writing, the Bidder shall continue to perform its obligations under the Contract as far as is reasonably practical, and shall seek all reasonable alternative means for performance not prevented by the Force Majeure event.

EXECUTION OF SERVICE LEVEL AGREEMENT

29. On completion of the Bid Process, the successful bidder(s) should execute a Service Level Agreement. Bidder(s) should also execute a Non- Disclosure Agreement in the Bank's Seal & Signature of Vendor

prescribed format. The agreement/ contract would be signed in Berhampur only and stamped as per **Odisha Stamp Act**. All the stamp duty shall be borne by the Bidder.

RESTRICTION OF FURTHER CONTRACTS

30. The Bidder shall not assign, in whole or in part, its obligations to perform under the Contract, except with the Bank's prior written consent. Consortium and joint venture responses are not allowed, in any case. Also, bidders have to note that no sub-contracting/ sub-letting is allowed.

AMENDMENTS TO CONTRACT

31. No variation in or modification of the terms of the Contract shall be made, except by written amendment, signed by the parties.

CONFIDENTIALITY OF CONTRACT DOCUMENTS & INFORMATION

- 32. The Bidder shall not, without the Bank's prior written consent, disclose the Contract, or any provision thereof, or any specification, plan, drawing, pattern, sample or information furnished by or on behalf of the bank in connection therewith, to any person other than a person employed by the Bidder in the execution of the Contract.
 - a. Disclosure to any such employed person shall be made as confidential and shall extend only as far as may be necessary for purposes of such performance.
 - b. The Bidder shall not, without the Bank's prior written consent, make use of any document or information except for purposes of performing the Contract.
 - c. Any document, other than the Contract itself, shall remain the property of the Bank and shall be returned (in all copies) to the Bank on completion of the Bidder's performance under the Contract, if so required by the Bank.
 - d. Bidder to submit Audited Balance Sheets & FRs within 6 months of close of financial year of the successful Bidder, failing which Bank will withheld payments. Bank will scrutinize the FRs and may decide to continue the contract or terminate.

PUBLICITY

33. Any publicity by the bidder in which the name of Indian Bank is to be used should be done only with the explicit written permission of Indian Bank.

AUTHORIZED SIGNATORY

- 34. All pages of this TENDER document and corrigenda must be stamped and initialed by the authorized signatory of the bidder confirming acceptance to all terms and conditions of this TENDER and should be submitted as part of the technical bid.
 - a. After completion of selection process the Bank will finalize the contract with the selected Bidder(s). To ensure this both the parties shall also be liable to make authorized officials to be present for discussions.
 - b. The Bidder(s) shall submit a Board resolution in case of a company and/or authorization letter duly signed by the authorized signatory naming the official(s) who shall be authorized to hold discussions, time and venue of which shall be intimated to the

successful bidder in writing at least 3 calendar days in advance.

READ THE TENDER DOCUMENTS CAREFULLY BEFORE SUBMISSION

Annexure-I

Application for participation in TENDER for New installation, repair and maintenance of Fire Alarm System (Including maintenance of existing Fire Alarm System, Burglar Alarm System and CCTV) (TO BE TYPED ON THE BIDDER'S PRINTED LETTER HEAD)

The Zonal Manager, Indian Bank Zonal Office Plot No.704/7172 and 704/7174 1st Floor Sri Krishna Vihar Chowk Main road, Ambapua, Berhampur, Odisha-760011

Dear Sir,

Subject: Application for participation in Tender for New installation, repair and maintenance of Fire Alarm System, Burglar Alarm System and CCTV (including maintenance of existing Fire Alarm System, Burglar Alarm System and CCTV)

- 1. This has reference to the captioned subject, I/We have carefully perused and understood the criteria mentioned in the Tender Notice released on the website of the Bank.
- 2. Accordingly, I/We now submit the application form duly completed in all respects, together with certified copies of the following documents as required by you for participation in Tender for New installation, repair and maintenance of Fire Alarm System, Burglar Alarm System and CCTV (including maintenance of existing Fire Alarm System, Burglar Alarm System and CCTV) to your bank.
- 3. I/We confirm that all information given herein is true to the best of my/our knowledge. I/ We also understand and confirm that if any of the information given is found to be incorrect either fully or partially or any false/fake document is submitted at any stage, you may reject the application summarily and also take any legal action as per law.
- 4. It is also confirmed that, I/We hereby agree with all the terms and conditions laid down in the application/empanelment documents.

Yours faithfully,

(Proprietor / Bidder's Signature, Name with Seal)

Seal & Signature of Vendor

Encl: Documents: -

Annexure-II

BIDDER PROFILE/ TECHNICAL BID (TO BE TYPED ON THE BIDDER'S PRINTED LETTER HEAD)

SI No	Subject	Details
1.	Name of the Manufacturer/ Firm/ Company/ Dealer/ Vendor	
2.	Year of Establishment	
3.	Constitution of the Firm (whether Proprietary/ Partnership/ LLP/Pvt. Ltd./Public Ltd.)	
4.	Address of Head Office (in India), including	
	i) Email id	
	ii) Landline and Mobile Number(s)	
5.	Name of the Proprietor/Chairman/ Managing Director/CEO/ Country	
	Head (as the case may be)	
6.	Name(s) and Address of Office at Districts of Odisha including	
	i) Email id	
	ii) Landline and Mobile Number(s)	
	(Please attach Lease Agreement/ Registration Certificate under Shops	
	and Establishment Act)	
7.	Date of opening of company's Office at Districts of Odisha	
8.	Whether registered with the Registrar of Companies/Registrar of Firms	
	in India. If so, mention number and date and enclose Registration	
	Certificate copy.	
9.	Whether an assesses of Income Tax. If so, mention Permanent Account	
	Number and Taxpayer Identification Number. Furnish copies of Income	
	tax clearance certificate	
10.	Whether registered for GST purposes. If so, mention number and date.	
	Also furnish copies of GST certificate.	
11.	Copies of IT Returns last 03 years and GST Return of last one year	
12.	Is the Company/Firm a manufacturer of the Fire Alarm System, Burglar	
	Alarm System and CCTV equipment/ accessories/components, etc	
	required by the Bank? If Yes, name of the equipment/	
	accessories/components, etc and place where manufacturing unit is	
	located. (All manufactured products	
	should be BIS certified)	
13.	Is the vendor having URC (Udayam Registration Certificate). If Yes,	
	submit the relevant certificate.	
14.	Have you been prequalified by PSUs / Banks (Public/Private)/NBFCs/	
	Government Departments etc. for New installation, repair and	
	maintenance of Fire Alarm system? If Yes, furnish their names,	
	category and date of empanelment. (Enclose empanelment letter)	

15.	Do you have presently running contract with PSUs/ Banks (Public/Private)/NBFCs/ Government Department, etc. for New installation, repair and maintenance of Fire Alarm System? If yes, enclose Performance report/ certificate of running contract.	
16.	Details of Technicians positioned at 2 districts mentioned in this	
	TENDER, in format:	
17.	Details of EMD Enclosed	
18.	Details of relative(s) employed in Indian Bank and erstwhile Allahabad	
	Bank, if any.	
	Name:	
	Relation:	
	Branch/Office:	
	Branch/Office last served (if retired):	
	Contact Details:	

Declaration

- 1. I / We have read and understood the tender documents and I / We understand that if any false information is detected at a later date, any contract made between ourselves and Indian Bank on the Basis of the information given by me / us can be treated as invalid by the Bank and I/ We will be solely responsible for the consequences. I / We agree that the decision of Indian Bank in selection of bidders/contractors will be final and binding to me /
- 2. I / We agree that I / We have no objection if enquiries are made about the work listed by me / us here in above and/or in the accompanying sheets.
- 3. All the information furnished by me/us above here is correct to the best of my/our knowledge and belief.
- 4. I/We the authorized signatory of the firm undertake to state that our Firm has proper infrastructure and resources and is capable of undertaking New installation, repair and maintenance of Fire Alarm System, Burglar Alarm System and CCTV (including maintenance of existing Fire Alarm System, Burglar Alarm System and CCTV) installed in 43 branches/offices of Indian Bank including all rural areas. We further undertake to state that we would be supplying all spare parts of quoted modules for a minimum period of 03 years from the date of Installation.

	Signature
Place:	Name:
Date:	Designation:
Seal of the Company	(Authorized Signatory)

Annexure-III

LIST OF ENCLOSURES

TO BE ATTACHED WITH TECHNICAL BIDS

SI No	Subject	Enclosed (Yes/No)
1.	Certificate of Registration of company/dealership	
2.	Certificate of registration with Income Tax, GST, EPF,ESI, VAT, TAN/TIN etc	
3.	Details of company owned registered office at BERHAMPUR with names of employees, address, Tel no., etc	
4.	IT Returns and GST Return	
5.	Empanelled with govt./public sector/banks	
6.	Presently running contract work order with govt./public sector/banks	
7.	STQC/ERTL/ETDC/ISO/BIS/DEALER certificate	
8.	Customer Reference (other than Indian Bank)	
9.	Documentation: - product, brochures, leaflets, manuals, warranty conditions etc.	
10.	Certificate that Authorized dealer/Firm/OEM or its Sister Agency have not been blacklisted	
11.	Document(s) in support of any other information	
12.	Bank Details (Account with Indian Bank, AMBAPUA/BERHAMPUR Branch)	
13.	EMD	

- Note: 1. In absence of any of the information/enclosures or/ and FAKE, WRONG, FICTICIOUS, FALLACIOUS, etc reporting, the tender is likely to be rejected
 - 2. The Vendor shall produce/provide original of any documents, required by the Bank for Verifications.

Annexure-IV

FINANCIAL BID

(TO BE TYPED ON THE BIDDER'S PRINTED LETTER HEAD)

(PRICE BID)

PRICE BID FOR FIRE ALARM SYSTEM AND COMPREHENSIVE AMC

(All rates to be quoted without GST)

	Name of the Firm		
Item	Specify Brand and Model		
1.	Control Panel		Rs.
	Zone Main Control Panel (Latest Microbased as per IS – 2189- 2008) with in manual OFF switch (in case continuous inbuilt SMPS, with a feature of conpower supply (in case of external power should indicate the health of the system Battery Status indicator, faulty Zone Indicator	built Auto Dialer, with bus fault alarm), with tinuous uninterrupted r supply failures). Panel n (Fault, Power Failure,	
	i) Inbuilt Auto Dialer with facilit Telephone/ Mobile Numbers eac at least 20 Seconds	•	
	ii) Message should be repeated dialling 2 nd number. In case of N facility to re- dial the number afte	umber not responded,	
2.	In Built Battery 2 Numbers of SMF (Sealed Maintenance 7 AH each], (The Battery Backup with capable of Providing 48 Hrs Standby Failure as per IS 15908/2011 & IS 2 operation for at least 30 Mins	built Battery Charger supply in case of AC	Rs. (For Two Numbers)
3	Ionization Smoke Detector Conform to 15908-2011/ IS 2189-2008 with LED indicator lamps, compatible Heat and multi sensor. Rate should be q	to work with Optical,	Rs.

4	Optical Smoke Detector Conform to 15908-2011/ IS 2189-2008 or Similar Standards with LED indicator lamps (Operation Principle- Light scattering/ Obscuration), compatible to work with Ionisation, Heat and multi sensor. Rate should be quoted per unit	Rs.
5.	Heat Detector Conform to IS 2175-1988/ IS 2189-2008 or Similar Standards with LED indicator lamps (Operation Principle- Light scattering/ Obscuration), compatible to work with Ionisation, Optical and multi sensor. Rate should be quoted per unit	Rs.
6.	Manual Call Point Conform to 15908-2011/ IS 2189-2008 or Similar Standards with hammer & chain, Glass of Minimum 2mm thickness, Alarm triggered by Breaking with LED Indicator Lamps. Rate should be quoted per unit	Rs.
7.	Electronic Siren/ Sounder Conform to IS 15908-2011/ IS 2189-2008 or Similar Standards, Min of 65 db output, Type of Sound – Intermittent/ Dual. Rate should be quoted per unit	Rs.
8	Response Indicator Conform to IS 15908-2011/ IS 2189-2008 with LED Indicator Lamp. Rate should be quoted per unit	Rs.
9	Wiring 2 Core 1.5 Sq mm Copper Conductor FRLS armoured and shielded Copper cable, ISI Marked. Rate should be Quoted per meter	Rs.
10	PVC Conduit Rigid PVS conduit 2 mm with ISI Mark & to be fixed with metal saddling at every 2 ft distance # Rate should be quoted per meter	Rs.
11	Installation & Delivery charges	
12	Package Cost (by adding SL. 1 to SL.11)	

13	Annual Service Charges for 1 Year (4 mandatory	
	quarterly visits) – Rate per system per Annum for AMC for	
	01 year after warranty covering replacements of Control	
	Panel, Sensors, MCP, Hooter, all other components &	
	wiring. Any numbers of Complaints to be attended free of	
	charge (Refer AMC	
	Clause)	

14	Warranty period for New Fire Alarm System.	Months
15	Buy back rate for complete old system of any Brand. (When replaced with new system)	Rs
16	Reinstallation Charge of Entire System (Within the same premises)	Rs
17	Shifting/installation Charge of Entire System (In Alternate premises)	Rs

4 Zone Fire Alarm System

Package Cost (by Adding SL. 1 to SL.11) in Words	:
Annual Maintenance Contract for 01 year in words	:
Buy Back Rate for Complete Old System	:
Place. Date.	Signature of Authorised Signatory Name & Designation & Seal of the Company

PRICE BID FOR BURGLAR ALARM SYSTEM AND COMPREHENSIVE AMC

(All rates to be quoted without GST)

	Name of the Firm		
Item	Specify Brand and Model		
1.	Control Panel 4 Zone Main Control Panel (Latest Microbased as per IS – 2189- 2008) with inlinbuilt LED indication, with inbuilt SM continuous uninterrupted power supply power supply failures). Panel should incosystem (Fault, Power Failure, Battery State Indication etc. The System should autidisarming) change from day to night methe real time clock (Programmable) and change manually too. System should autidisarmine of minutes (day/night mode) iii) Inbuilt Auto Dialer with facility Telephone/ Mobile Numbers each at least 20 Seconds iv) Message should be repeated dialling 2nd number. In case of Numbers facility to re- dial the number after #Rate should be quoted per unit	built Auto Dialer, with IPS, with a feature of y (in case of external licate the health of the us indicator, faulty Zone comatically (arming & ode & vice versa as per d also have option to utomatically reset after y to dial at least 5 th & voice message of at least twice before umber not responded,	Rs.
2.	PIR Sensor Should work on dual technology (IR & coverage horizontal angle 110 degrees, meters, with pet/ rodent immunity & p to adapt changes in ambient temper seasons # Rate should be quoted per unit	Detection range of 10 rovision for calibration	Rs.
3	Hooter Min 90 dB for internal and 110dB for tamper loop (Cutting of Hooter wire sh Hooter), ABS Body, Weather Proof # Rate should be quoted per unit for each	ould trigger the other	Rs(for 90 dB) Rs(for 110 db)
4	Magnetic Sensor ABS Body, 4 Wired with tamper loop (No Circuit) # Rate should be quoted per unit		Rs.

5.	Panic Switch	Rs.
	Sturdy built, Micro Switch Technology # Rate should be	
	quoted per unit	
6.	Vibration Sensor	Rs.
	# Rate should be quoted per unit	
7.	Heat Sensor	Rs.
	# Rate should be quoted per unit	
8.	<u>Wiring</u>	Rs.
	Core 1.5/ .75 Sq mm, Flexible, ISI Marked (Finolex/ Plaza/	
	Polycab/ RR Cable or similar quality), PVC insulated copper	
	wire for connection of panic switches and other sensors	
	respectively. # Rate should be quoted per meter	
9.	PVC Conduit	
	Rigid PVS conduit 2 mm with ISI Mark & to be fixed with metal	
	saddling at every 2 ft distance	
	# Rate should be quoted per meter	
10	Installation & Delivery charges	
11	Package Cost (by adding SL. 1 to SL.10)	
12	Annual Service Charges for 1 Year (4 mandatory	
	quarterly visits) – Rate per system per Annum for	
	Comprehensive AMC for 01 year after warranty covering	
	replacements of Control Panel, Sensors, MCP, Hooter, all	
	other components & wiring. Any numbers of Complaints	
	to be attended free of charge	
	(Refer AMC Clause)	
13	Warranty period for New Burglar Alarm System.	Months
14	Buy back rate for complete old system of any Brand.	Rs
	(When replaced with new system)	
15	Reinstallation Charge of Entire System (Within the same	Rs
	premises)	
16	Shifting/installation Charge of Entire System (In Alternate premises)	Rs

4 Zone Burglar Alarm System

Package Cost (by Adding SL. 1 to SL. 10) in Words:			
Annual Maintenance Contract for 01 year in words	:		
Buy Back Rate for Complete Old System	:		
Place.	Signature of Authorised Signatory		
Date.	Name & Designation & Seal of the Company		

PRICE BID FOR NVR BASED CCTV SYSTEM AND COMPREHENSIVE AMC

(All rates to be quoted without GST)

	(All rates to be quo	neu without GST)	
	Name of the Firm		
	Specify Brand and Model		
1.	Network recorder (NVR)	A -late with a -late -late	Eight Ch NCR
	8/16/32 Channel NVR with 2 / 4 SATA supporting minimum 6 TB Hard Disk . F		Rs.
	resolution minimum of 12 TB of Hard disadequate back up of 90 days. The NVR		Sixteen CH NVR
	Over Ethernet (POE) for reduced cabling audio. Should support third party can	. Should support 2 way	Rs.
	recording from Minimum 6 MP IP c conform to all other specifications menti	ameras or more and	
2.	Hard disk - Surveillance Grade		(For Two Hard Disks)
	6 TB * 2 disks with 2 years warranty (Seagate / WD or equivalent)		Rs.
3	IP camera – HD IR Verifocal Lens Bullet	: Camera 2 MP – To	Rs.
	be set to		
	15 Frames Per Second (FPS)		
	2MP :: 1/2.8" Progressive CMOS, ICR, Olux with IR,		
	1920x1080:25fps(P)/30fps(N), H.265+/H.265/H.264/MJPEG,		
	DC12V & PoE, 3D DNR, BLC, IR range: up to 50m, Support on-		
	board card slot -S: Audio/Alarm IO connectors & Conform to all		
	other specifications mentioned above		
4	IP camera -HD IR Fixed Lens Dome Camera 2 MP - To be set		Rs.
	to 15		
	<u>Frames Per Second (FPS)</u>		
	2MP :: 1/2.8" Progressive CMOS, ICR, 0lux with IR, Effective		
	Pixels:1920x1080: with video frame rate 25fps(P)/30fps(N),		
	H.265+/H.265/H.264/MJPEG, DC12V & F		
	range: up to 50m, Support on-board care		
	IO connectors and conform to all other s mentioned above		
		oora (2 MD) with C4 CD	Dc
5.	One Standalone Vandal Resistant Can Memory Card	, ,	Rs.
	(Image sensor:1/2.8" progressive scan C		
	illumination:0 lux with IR, Colour- 0.01 l	·	
	0.028 Lux F 2.0 AGC ON), (Max resolution other specifications as mentioned above		
	Unier specifications as mentioned abov	e	

6.	Network Switch for NVR and Cameras	Rs.		
	Unmanaged Poe, 8 100M Poe, 1 100M uplink port, 250m			
	Transmission, 6KV Surge Protection, 58W			
7.	Network Cable	Rs.		
	Cat 6 (T P link) Cabling BIS certified (Rate for 100 Mtrs)			
8.	16"/17" Monitor (Make: LG/ Samsung or equivalent)	Rs.		
_	Minimum Resolution: 1920x 1080 pixels full HD			
9.	Wireless Mouse	Rs.		
10.	Compatible 2U/4U/6U Rack (wall mount)	Rs (2U)		
	Power strip 6 socket power supply & conform to all other			
	specifications mentioned above	Rs (4U)		
		Rs(6U)		
11	Installation & Delivery charges	Rs.		
	, J			
12	Package Cost (by adding SL. 1 to SL.11)			
13	Annual Service Charges for 1 Year (4 mandatory quarterly	Rs.		
	visits) – Rate per system per Annum for Comprehensive AMC for			
	01 year after warranty covering replacements of NVR, Hard Disc,			
	Cameras & all			
	other components & wiring. Any numbers of Complaints to be			
	attended free of charge (Refer AMC Clause)	NA d		
14	Warranty period for New NVR CCTV System.	Months		
15	Buy back rate for complete old system of any Brand. (When	Rs		
	replaced with new system)			
16	Buy back rate for old major components of any Brand (when	Rs		
	replaced with new) viz- NVR, Camera IR Bullet, IR Dome &			
	Monitor			
17	etc.	RS		
17	Installation & Delivery Charge for components, when not covered in AMC (NVR, Camera, Monitor & Hard Disc)	1.5		
18	Reinstallation Charge of Entire System (Within the same premises)	Rs		
	The instance of the system (Within the sume premises)			
19	Shifting/installation Charge of Entire System (In Alternate	Rs		
	premises)			

Package Cost in Words (From SI 1 to SI 11)	:
Annual Maintenance Contract for 01 year in word	ls:
Buy back rate for complete old system in Words	:
Place.	Signature of Authorised Signatory
Date.	Name & Designation & Seal of the Company

Other Terms & Conditions for NVR Based CCTV Systems

- a) Minimum warranty for all products is 1 year.
- b) Warranty for Surveillance HDD should be minimum 2 years.
- c) Cost should be inclusive of delivery, installation and commissioning. Additional charges will not be applicable.
- d) 04 quarterly visits towards preventive maintenance should be carried out during the warranty period of 1 year.
- e) Vendor should be capable for giving Annual Maintenance Contract (Comprehensive or Non Comprehensive) for at least 03 years post completion of warranty. However, awarding of AMC is fully under the discretion of Bank.
- f) EMD for an amount of <u>Rs. 5,000/-</u> in the form of Demand Draft in favour of Indian Bank Zonal Office, Berhampur payable at **Ambapua** should be enclosed along with the sealed quotation.

Place.	Signature of Authorised Signatory
Date.	Name & Designation & Seal of the Company

25. Deliverables & Timelines

The Vendor should ensure that the defects reported in the FIRE EXTINGUISHER supplied to the Bank on any working day is set right within two days and in no case later than the two working day. In case, the system or any equipment cannot be repaired within the stipulated period, the Vendor should provide a replacement till the system/ equipment is returned duly repaired.

26. SPECIFICATION/REFILLING/MAINTENANCE

A QUARTERLY VISIT TO THE BRANCHES SHALL BE MANDATORY FOR CHECKING THE PRESSURE AND CONDITION OF ALL THE FIRE EXTINGUISHERS

a) SPECIFICATIONS FOR PORTABLE FIRE EXTINGUISHER CARBON DIOXIDE 4.5 KGS

S No	Values	Specification	
1.	Scope of work	Supply of Portable CO₂ extinguisher 4.5 kgs-	
		confirming to IS -15683: latest revision and ISI	
		marked complete with all fittings.	
2.	Extinguishing Media	CO ₂ used in extinguisher shall of Comply IS 15222.	
3.	ULC fire rating	10-B:C	
4.	Cylinder Material	Mild steel.	
5.	Valve Material	Plated Brass	
6.	Handle/lever Material	Stainless steel	
7.	Operating Pressure(@70 deg F)	850 PSI	
8.	Temperature Range(Deg C)	-30 degree cent. to 55 degree Cent.	
9.	Nominal discharge time (Sec)	10-18 sec	
10.	Discharge horn	Non -conductor of electricity.	
11.	Hose	Min. bursting pressure shall be 275 kgf/cm2.	
12.	Discharge Range (mtr)	01-2.4	
13.	Operating type	Squeeze grip, Screw Grip	
14.	Test Report & certificates	IS approved Certificate.	
	Recommended area for		
15.	Utilization	Electrical/Electronics/inflammable liquid.	
		Extinguisher permanently marked with the	
		following information:	
		a) Manufacture's Name or Trade -mark,	
16.	Marking	b) Year of Manufacture of the cylinder and test	
	-	pressure.	
		c) Method of operation in prominent letters.	
		d) ISI Marking, CE marking	

min

Refilling/Maintenance Of 4.5 Kg Co2 Fire Extinguisher

- 1. Every carbon Di-oxide extinguisher installed in premises shall be hydraulically pressure tested once in 5 years. There shall not be any leakage or visible distortion. Extinguisher which fails in these requirements shall be replaced.
- 2. Always discharge gas from extinguisher by getting it operated by the Bank Staff, before sending for HPT and refilling.
- 3. Refilling should be done when cylinder weight is reduced by 10% or more than 10% from gross weight of Cylinder or after Hydraulic pressure test (HPT).
- 4. The vendor license and demand for supply of HPT certificate after HPT of Cylinder shall be checked.
- 5 Fire Extinguisher shall comply with IS 15683:2018.
- 6. Maintenance to be done in accordance to IS 2190:2010.
- 7. Shelf life of carbon Di-oxide extinguishers is 15 years only, from manufacturing date.

b) SPECIFICATIONS FOR PORTABLE FIRE EXTINGUISHER STORED PRESSURE 4 KGS ABC TYPE

Refilling/Maintenance Of 4.5 Kg ABC Fire Extinguisher

1. Every Dry chemical powder extinguisher installed in premises shall be hydraulically pressure tested once in 5 years. There shall not be any leakage or visible distortion. Extinguisher which fails in these requirements shall be replaced.

Capacity	Working Pressure (KGF/CM2	Testing Pressure (KGF/CM2)	Area Protection (L*B)	Volume Protection (L*B*H)	Operation Time (Second)	Hanging Vertically above risk
5 Kgs	7 to 10	35	3.5 to 4 m2	8 m3	10-15	1.5M to 2M
10 Kgs	7 to 10	35	7 to 8 m2	15m3	15-20	1.75M to
						2.25M

- 2. Always empty out Powder from extinguisher before sending for HPT and refilling.
- 3. Refilling should be done when pressure is drop 10% or more than 10% in stored pressure type and caking of powder in DCP cartridge type or After Hydraulic Pressure test (HPT).
- 4. Checked, the vendor license and demand for supply of HPT certificate after HPT of Cylinder.
- 5. Fire Extinguisher shall comply with IS 15683:2018.
- 6. Maintenance to be done in accordance to IS 2190:2010.
- 7. Shelf life of DCP extinguisher is 10 years only, from manufacturing date.

c) AUTOMATIC MODULAR FIRE EXTINGUISHER

ABC Dry chemical powder Automatic Modular Fire Extinguisher, the release temperature can be adjusted to suit prevailing conditions.

Technical Data

Utilization Temperature: 57 degree cent. to 107 degree cent.

S No	Values	Specification		
1.		Supply of Portable extinguisher 4 kgs-confirming		
	Scope of work	to IS -15683: latest revision and ISI marked		
		complete with all fittings.		
2.	Extinguishing Media	MONNEX.		
3.	ULC fire rating	3A,55B		
4.	Cylinder Material	Mild Steel		
5.	Valve Material	Plated Brass		
6.	Handle/lever Material	Stainless steel		
	Operating Pressure(@70			
7.	deg F)	15 KGF/CM2		
8.	Temperature Range(Deg C)	-30 degree cent. to 55 degree Cent.		
^	Nominal discharge time			
9.	(Sec)	10-20 sec		
4.0		Flexible PVC braided hose fitted with end		
10.	Discharge horn	connection.		
11.	Hose	Min. bursting pressure shall be 55 kgf/cm2.		
12.	Discharge Range (mtr)	2 Mtr		
13.	Operating type	Squeeze grip		
14.	Test Report & certificates	IS approved Certificate.		
	Recommended area for	Class A, B and Ci.e. Wood, Paper, Petroleum and		
15.	Utilization	electrical equipment.		
		Extinguisher permanently marked with the		
		following information:		
		a) Manufacture's Name or Trade-mark,		
16.	Marking	b) Year of Manufacture of the cylinder and test		
	-	pressure.		
		c) Method of operation in prominent letters.		
		d) ISI Marking, CE marking		
ye an anna an a		· Nin		