

Schedule of quantity for furnishing of Delhi Chungi Meerut Branch

S no	Description of Item	Qty	Unit	rate	Amount
1	Low Height Partition -Providing & Fixing of Low Height Partition (Solid) with 8mm glass Up to ht. of 4'-0" in Banking hall laminated and inclusive of door. Made of 2"x2" aluminum tubular section framework (18 gauge) 2'0" c/c both ways 10 mm MDF BOARD of approved make on both faces finished with 1mm thick laminate of approved shade. Till the height of 3'-3" and 1'-3"(10mm thk.) toughened glass on top complete with teak beading, The spirit polishing teak sections of approved shade as per drawing Complete in all respects.	220	Sft.		
2	Providing and fixing 600 mm x 600 mm mineral fiber tiles false ceiling of Armstrong/Gypboard/equivalent approved make of micro look system including suspension system as per manufacturer's specifications and instructions of Bank complete in all respects including making cutouts where necessary for electrical lighting fittings etc. complete all as directed by the Bank. (As per site requirement)	1000	sqft		
3	Partly Glazed Full height Partition – Providing & fixing of full height party glazed partitions as per drawing and conforming to the following specifications : (century ply, green ply or Duro ply) Made of partly glazed (8 mm toughened glass of approved make as per design), made of 2"x2" aluminum tubular section framework (18 gauge) 2'0" c/c both ways 10 mm MDF BOARD of Approved Make on both faces finished with 1mm thick laminate of approved make & shade The work includes providing a 6" x 9" voucher cut out with tray, spirit polishing of shade on woodwork and steam beach beading etc. Including doors but including cost of door closers mortise locks. Complete in all respects. glazing : Cash Cabin 8 mm. thick clear float glass fixed with continuous steam beech/teak wood glazing beads of approved shape (finished 35x25 mm) all round polished and coated with NC lacquer finish. The rate should also include cost for decorative etching on one side of the glass Quoted rates shall include all necessary materials accessories and labor and also allow provisions for electrical /telephone/computer wiring conduits and switch boxes etc.	185	Sft.		
4	GLASS DOORS WITH ALUMINIUM FRAME & FIXED GLAZING (ATM & MAIN ENTRANCE) Providing and fixing aluminium door and glazing consist of 16 gauge powder coated section 100X35MM,75x35mm as per requirement with powder coated aluminum beading , necessary rubber gaskets and 6mm thick. Clear glass including all necessary hardwares , handles, mortice lock, floor spring, door stopper etc. complete in all respect. Complete as per design	102	Sft		
5	Providing and fixing Flap Door of min. size: 3' (B) X 2'6" (H) made of block board with approved lamination on both side, of required size with hinges/tower bolts/stopper/handles etc complete.	2	Nos		
6	Supply and erecting wall mounted customer writing ledge of approx. size 1200x230mm, top made of 12mm thick float glass and sides/bottom etc., made of 19mm thick BWP grade block board finished with 1mm thick laminate of approved shade and quality. Rate to include making of suitable nos. of boxes of suitable sizes to keep different types of slips/leaflets etc. finishing edges with 6mm thick polished steam beach wood lipping. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer.	1	each		
7	Providing and fixing customer writing table 900mm circular made of 12 mm thick ply board supported on pedestal with necessary fixtures. The top to be provided with shelves for keeping forms/slips etc. all exposed surface to be paste with mica to match the ambience.	1	Nos		
8	Providing and fixing cheque drop box / Suggestion box of size 450mm 750mmx300 mm with a slit opening of 10mmx150 mm and openable shutter of 250x262mm size with glass fixed above 1.5 m above ground level. All exposed surface to be pasted with matching laminate and inside with .1mm liner mica. The cost includes that of necessary fittings.	2	Nos		
9	Providing and fabrication of table (with keyboard tray) having table body of 18mm, 12mm & 6mm thick plywood and table top & shutters of 19mm thick block board. The drawer unit must have one drawer mounted on drawer slider and shuttered shelf under it. A readymade metallic keyboard tray must be fixed under the table top. A round, PVC cable crossing socket (cable manager) must be fixed on the table top for power/data cable crossing. A foot rest, made of 19mm thk block board must be fixed and a CPU carrier, on the footrest level must be fixed. The table top and all other exposed surfaces must be covered with 1.0mm thk laminate. All inside/hidden surfaces must be finished with one coat of primer and three coats of synthetic enamel paint. All the edges and corners must be protected with 6mm thick plain teak wood bead. 4" high skirting. must be fixed on exposed surfaces. All the teak wood must be finished with 3 coats of synthetics paint. Automatic locks and handles must be fixed in drawers & shutters.				

i	Branch Manager Table Table- 1675 mm x 750 mm x750mm Side Unit 1050mmx375mmx375mm Table top with 5mm float glass	1	No		
ii	OFFICER TABLE & SIDE UNIT Table Size - 1375 mm x 750 mm x750 mm Side Unit 1050mmx375mmx375mm	1	Nos		
10	Providing and fixing 1.5x 4/5 feet 12 mm toughened Glass on all tables /counters complete as per drawing including glass support. Glass has to fixed as vertical partition in the front end of the counter including all fittings and fixtures required for fixing of glass (towards customer side) to restrict direct access of customer.	50	Sft		
11	Supplying and erecting clerical counters (running tables) 750mm deep and 750mm high including drawer-cum-cabinet unit for files, space for computer CPU, wire managers, modesty panel, tea tray etc. made with 19mm thick BWP grade block board on top and supporting sides / front with necessary well seasoned Malaysian Sal/ Kail/ Marandi wood frame work, finished on top with mirror polished 18mm thick granite slab (Jet black) with rounded edges and sides with 1.0 mm thick laminate of approved shade and quality, including providing and fixing 450mm long key board tray of approved shade, hardware and accessories at each of the counter. All exposed edges of block board are to be provided with half round teak wood moldings, duly polished and 100mm high laminate of approved make & shade all as directed. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer. Skirting: 100mm high laminate of approved make & shade all as directed. Rate to include charges for brass hardware fittings as well as fixtures like sliding gear for drawers of 'Earl Behari' or equivalent approved make.	20	Rft		
12	Providing and erecting in position Cash Work Station of approx. size 1370x900x750mm (4.5'x3.0'x2.5'), made of 19mm thick block board pasted with 1.00mm laminate inclusive of a 350mm wide customer top at 1155 mm level,. Writing top & customer top should be finished with mirror polished; 18mm thick granite slab (Jet black) with rounded edges and sides with 1.0mm thick laminate of approved shade/make. Both should have sufficient gap in between to accommodate computer monitor up to full depth. The workstations shall be supported from the partition system made of 19mm thick BWP grade block board finished with 1.00 mm thick laminate of approved shade/make. Free edges shall have 18 mm thick, polished white or steam beach wood moldings of half-round profile as per drawings and instructions and 100mm high laminate of approved make & shade all as directed. Each cash workstation shall comprise of the drawer unit, Tea tray at top, Cash drawers with approved telescopic channels for drawer-slides, automatic locks (keys in duplicate), wire managers, space for computer CPU, modesty panel and other necessary hardware and accessories including satin finish S. S. handles of approved quality. Inner face of cash counter to be provided with 16G, M.S. sheet, painted with two coats of synthetic enamel paint of approved shade & make, over a coat of approved steel primer. Inner faces shall be painted with two coats of synthetic enamel paint of approved shade & quality over a coat of primer.Skirting: 100mm high laminate of approved make & shade all as directed.	9	Rft		
13	Providing & fixing 12mm thick clear float glass on Cash Counters at front & sides, with SS clamps/patch fittings, necessary polished beadings etc complete all as directed by the Bank. Note: Front glass to be fixed in slanting position towards inside cash area with required angle as directed. Above glass to be fixed either in two pieces. Lower piece having one semi-circular/rectangle 6" dia/long opening at customer top level & other piece to be fixed at suitable height making 3" slit for conversation with customer. In this case, only glass area to be measured for payment purpose.) In case of single piece, one semi-circular/rectangle 6" dia/long opening at customer top level & one circular hole of required dia at suitable height for conversation at centre of cash counter to be provided.	27	sft		
	Supplying and fixing in position overall 32 mm thick solid core hot pressed phenol formaldehyde bonded flush door finished with 1.0 mm thick laminate of approved shade and quality on both sides of the door shutter & beading on edges including cost of hardware fittings e.g. Godrej night latch / mortise lock, hinges, door closure, handles etc. of approved make and quality & making provision of peep hole of suitable size with glass& beading all round all as directed. (Cash/Store/other doors)	33	sft		
	TOTAL				
	GRAND TOTAL				
	GST Paid Extra				

SR.	DESCRIPTION	MAKE / BRANDS
1	HDF. (High Density Fibre Board) – CONFIRMING TO IS : 12406 - 2003. (Density: 750 – 850 Kgs/m ³) colour code follow as per Bank Norms.	CENTURY/GREENPLY/Archid
2	PLYWOOD – BWP (Boiling Water Resistant, Termite Resistant & Borer Resistant) – CONFIRMING TO IS: 303.	CENTURY/GREENPLY/Archid
3	BLOCK BOARD – CONFIRMING TO IS : 11255 - 2003.	CENTURY/GREENPLY/Archid
4	FLUSH DOOR – CONFIRMING TO IS : 2202 (Part – 1) – 1991.	CENTURY/GREENPLY/Archid
5	LAMINATE – CONFIRMING TO IS : 2046-1995.	CENTURY/GREENLAM/Archid
6	Lipping & Moulding	First Class Teak Wood
7	Gypsum ceiling	Gypsum India, Saint -
8	Grid Ceiling	Armstrong, Dexune
9	GI Support system for False Ceiling	GYPSTEEL ULTRA
10	Adhesive	Fevicol SH.
11	Locks/Handles & all other hardware	Godrej, Dorset
12	Glass	Modi float/Asahi(Tata), Saint Gobain
13	Aluminium	Jindal/Hindal/Indal
14	Door Closer	OZONE/Dorma
15	FLOOR SPRING	OZONE/GODREJ
16	Paint	Nerolac / Asian Paints
17	Wood Preservative	Bison by British Paints /
18	Preservative	Solignum/Black Japan /

NOTE:

- 1- The contractor is strictly advised to use the makes specified/approved by the Bank/Architect, unspecified items will not be paid until they are changed with the specified ones.
- 2- The Plywood used for the work shall be BWR (Boiling water proof range) confirming to IS 303.
- 3- No escalation shall be paid to the contractor for material or labour.

Place:

Date:

Signature of contractor with seal