

PART-B

TENDER DOCUMENT

(SPECIFICATION & QUANTITIES)

**PROPOSED INTERIOR FURNISHING, WORKS OF "INDIAN
BANK- BRANCH- NIKARIGHATA, DISTT- SOUTH-24 PgS (WB**

INDIAN BANK, ZONAL OFFICE, KOLKATA SOUTH

**QUOTED RATES FOR PROPOSED INTERIOR FURNISHING WORK OF, INDIAN
BANK, BRANCH-NIKARIGHATA, DISTT- KOLKATA SOUTH (M.S.)**

S. NO.	WORKS	AMOUNT
		(Rs.)
1	TOTAL QUOTED AMOUNT FOR INTERIOR FURNISHING	
2	TOTAL QUOTED AMOUNT FOR FURNITURE WORKS OF BRANCH	
3	TOTAL QUOTED AMOUNT FOR ELECTRICAL WORKS	
	TOTAL RS.	



Signature of Contractor

BOQ OF FURNISHING JOB FOR NIKHARIGHATA BRANCH

SR.NO.	DESCRIPTION	QTY	UNIT	RATE	AMOUNT
	PART A: INTERIOR FURNISHING WORK				
	FURNISHING WORK				
1	POP & FALSE CEILING WORKS				
a	False Ceiling				
	Gypsum board Ceiling - 12.5mm th. single layer gypsum board fixed on suspended main G.I.channels 60 mmx 36 mm and secondary grid made of 45 mmX 18 mm all as per manufacturers' specifications, including jointing, finishing with gypsum compound, jointing tape and top coat. The surface shall be duly sanded and finished. Rate shall include making all the necessary cutouts for lights, grills,diffusers etc. The rate shall also include providing perimeter channel for grills, lights, diffusers as called for in HVAC and Electrical Drawings.The rate shall also include providing for edge/ angle bits at all corners,drop, necessary taping, filling with jointing compound as per manufacturers specifications. The rate shall be exclusive of trap door which shall be paid for separately. Cost to be quoted including painting.	680.00	Sq.ft		
b	GRID CEILING: 24"x24" Grid False Ceiling (SILHOUTE GRID): Providing and Fixing False ceiling Grid using hot dipped Galvanised steel sections, exposed surface chemically cleaned capping pre-finished in baked polyester paint. Main tee of size 3000 x 32 x 24 mm at every 1200mm c/c maximum, 1200mm cross Tee of size 1200 x 27 x 24mm at every 600mm intervals and 600 mm cross Tee of size 600 x 25 x 24mm at every 1200mm max and 3000 x 19 x 19mm wall angle all around the wall to form grid size of 600mm x 600mm . The Main grid to be suspended to the MS frame with 2mm pre-straightened GI wire and GI adjustable clamp and Laying of fibre wool board having Fire rating of 60 min. as per BS 476/23 of 1987 , Noise reduction co-eff. (NRC) of 0.50, Light reflectance of 83%, Sound attenuation of 32db, thermal conductivity of k=0.052 W/m, wt of 4kgs/mts and humidity resistance of RH-95 , with paint finish of 600x600mm x 12mm thick over the Grid. All as per the design and instructions Architects.	600.00	Sq.ft		
2	CARPENTRY AND INTERIOR WORKS				
1	PARTITION WORKS				
a	SOLID PARTITIONS (upto 8'6"-9'0")				
i	SOLID PARTITION - LAMINATED: Providing and fixing of full height solid partition made of salwood framework of size 50mm x 50mm fixed @450mm c/c bothways and covered with (6mm thk) BWR/BWP Ply make and finished with 1.0mm thk laminate of approved shade on both sides. 3" wide skirting to be shown in the laminate by way of 1mm wide groove.	228.00	Sq.ft		
b	GLAZED PARTITIONS				
i	FULLY /SEMI GLAZED PARTITIONS: Providing & fixing of fully glazed partitions by using the wooden frame work and ply comprising of A) The glazed portion out of 10mm thk glass fixed with internal framing and beading as per design. B) (6mm thk) BWR Grade ply of on both sides of frame + Laminate as per drawings.Glass of asahi/saint goblin / modi gaurd make. Wooden framework of size 50mm x 50mm fixed @450mm c/c bothways	202.00	Sq.ft		
ii	MAIN FIXED GLAZING: P/F of full height glazed partition for front glazing at Main Entrance made with 12mm Toughen Glass with white paint design with necessary additional supports as directed. Fitting should be with "patch fitting".	58.00	Sq.ft		
iii	SEMI-GLAZED PARTITIONS: Providing & fixing of semi glazed partitions upto 7'-0" ht .the partitions is made by using the Wooden frame work and ply comprising of A) (9mm thk) BWR Grade Marine ply of (Alishan/Greenply or Century Ply make)on both sides of partition as per drawings. Wooden framework of size 50mm x 50mm fixed @450mm c/c bothways. B)The glazed portion out of 10mm thk glass fixed with internal framing and beading as per design Glass of asahi/saint goblin / modi gaurd make.	222.00	Sq.ft		
iv	SEMI-GLAZED LOW HEIGHT PARTITIONS: Providing & fixing of semi glazed partitions upto 4" ht & glass to be fixed above or cover with SS round pipe.The partitions is made by using the Wooden frame work and ply comprising of A) (9mm thk) BWR Grade Marine ply of (Alishan/Greenply or Century Ply make)on both sides of partition + Laminate upto 3'-0" ht as per drawings. Wooden framework of size 50mm x 50mm fixed @450mm c/c bothways. B)The glazed portion out of 10mm thk glass fixed with internal framing and beading as per design Glass of asahi/saint goblin / modi gaurd make.	40.00	Sq.ft		
c	LOW HEIGHT SEMI SOLID PARTITIONS				
i	Same as item 1.b-(i) above but low height solid partition to have 12mm thick clear float glass of 300mm high fixed by way of wooden beedings . The glass edges to be machine polished and rounded at the corner. Wooden framework of size 50mm x 50mm fixed @450mm c/c bothways	-	Sq.ft		
3	PANELLING WORKS				



a	ONLY PANELLING WITHOUT FRAME: P/f paneling without wooden framework but 9mm thick plywood BWR Grade Marine ply of (Alishan/Greenply or Century Ply fixed on leveled wall and finished with 1.00mm thk. laminate of approved make and shade, on all exposed surfaces on all exposed surfaces as per details and design.	-	Sq.ft		
b	PANELLING: P/F paneling with wooden framework of size 50mm x 50mm with 450mm c/c made out of salwood treated with antitermite solution. 9mm thick plywood BWR Grade Marine ply of (Alishan/Greenply or Century Ply fixed on frame and finished with 1.00mm thk laminate having 3" wide skirting with 1mm thk groove between skirting and partition and 1mm groove between vertical laminates as per design.	200.00	Sq.ft		
4	DOORS				
i	P/f main entrance single leaf glass door for BRANCH/ATM ENTRY with 12mm thick Toughened glass. The beading to be polished matching the laminate shade. Rate to include cost of heavy duty floor spring (Everite / Hemco / Haldin / Hyper or equivalent of capacity 120 kg), SS handle of size 450mm, ball bearing hinges, mortise concealed dead lock, door stopper and all required hardware complete as directed.	2.00	Nos.		
ii	P/f Double Swing Branch Entrance Door & ATM fully glazed of overall size of 3'-0" x 7'-0" of 10thk toughened glass and vinyl film on it. Door to be fixed on floor spring.				
iii	Same as item no. 4(i) above but four side frame work made of Aluminium Anodised Sections of 18 gauge of approved shade and colour and 10mm thk toughened glass embedded in it.				
iv	Same as item no. 4(i) above but size of the door shall be 825mm x 2100mm. - FRAMELESS AND TOUGHENED				
v	Glass Door - BM Cabin				
	P/f Two side frame Cabin door fixed on floor spring finished in laminate from both sides with 10mm thk glass and frosted film on it. Door size 900mm x 2100mm	2.00	Nos.		
vi	P/f. Solid wicket gate door of size 900mm x 900mm made of 38mm thick flush door and mounted on heavy duty hinges for teller counter area.				
iv	Solid doors (with or without vision panel) For UPS, Service Area, Store, Pantry & Toilet Entrance Door				
	Providing & fixing Solid Flush Door of 38mm thickness in laminate finish on both sides With Vision Panel of size 300mm x 300mm made of 6mm thk glass. Door to be mounted on hinges and to be provided including Handles & necessary hardware fittings. the sizes of the doors to be considered as under:				
	i. IT/Electric Room Door : 975mm x 2100mm	1.00	Nos.		
	ii. Service Area door : 900mm x 2100mm	1.00	Nos.		
	iii. Store Room Door : 900mm x 2100mm	1.00	Nos.		
	iv. Pantry Door : 825mm x 2100mm	1.00	Nos.		
	v. Toilet entry Door : 825mm x 2100mm	1.00	Nos.		
	vi. CRM Entry Door : 975mm x 2100mm	-	Nos.		
	vii. Conference hall entry door: 975mmx2100mm	-	Nos.		
	viii. cash entry door:	2.00	Nos.		
5	STORAGE CABINETS				
i	Storage Full ht.				
	1' 6" deep x 7' 0" ht.				
	Carcass and shelves out of 3/4" and 1/4" thk. Marine ply of BWR Grade (Alishan/Greenply or Century Ply make)				
	Hardware - S.S. hinges, stoppers, 'Vijayan' locks, S.S. handles				
	Shutter (19 mm thk.) semi solid core faced with approved laminate (1.0 mm) on the exterior and back of shutter & Internal faces all finished with enamel paint of Asian make.	60.00	Sq.ft		
ii	Storage Half ht.				
	Size - 1' 4" deep x 2' 6" ht.				



	Carcass and shelves out of 3/4" and 1/4" thk. Marine ply of BWR Grade (Alishan/Greenply or Century Ply make)				
	Shutter (19 mm thk.) semi solid core faced with approved laminate (1.0 mm thk.) on the exterior and back of shutter and finished with enamel paint internally				
	Hardware -S.S. hinges, stoppers, 'Vijayan' locks, S.S. handles	36.00	Sq.ft		
6	COUNTERS AND DESKS				
	(COUNTERS) Providing and Fixing COMPUTER COUNTERS made out of 19 mm thick bwp grade board of approved brands as listed in the specifications, and as per the attached drawing, all complete with 1.0 mm thick laminate on all visible surface, tabletops, customer top, etc, and all drawers etc. to be painted with 1 coat of primer and 2 coats of 1st quality enamel paint). 12 mm thick glass, MODIGUARD / AIS, branded, to be used on top of the COMPUTER COUNTER. Keyboard Tray to be provided on Special Keyboard Slides, and wristrest to be given. Drawer Slides to be used for all drawers. All locks to be of Godrej. All drawers, cabinets, Keyboard, etc. to be lockable. Footrest to be provided. The Front of the Computer Counter shall have decorative finishing in ply and laminate as shown in the drawing attached. 12mm thick glass as a screen shall be provided in front, with a 3" gap from the counter top. Height of Glass: 12". Glass to be inserted in polished teakwood members, size 2" x 2", appropriately finished				
	3" high skirting box with walnut wood skirting, melamine polish finished				
i	BM workstations in laminate finish with side storage and back storage (size of storage 7'-0" X 2'-6" in height or as per the drawing) CRM Table size 7'x3' Or as per availability of space. The table shall be postformed	1.00	Nos.		
iii	Runing table for IT department	-	Rft		
iii	P/f Officers / Assistant Manager interactive workstations in laminate finish of Table size as per the Drawings. Table shall be postformed	2.00	Nos.		
iv	Senior officer table with interactive workstations in laminate finish. as per the drawings	1.00	Nos.		
v	Runing table for staff & daftari	4.00	Rft		
vii	CASH COUNTER				
	Providing and fixing top, front & side of cash counter made out of 18 mm BWP and termite proof blockboard as per design clad with 1.0 mm thk. Laminated on side and front & the edges to be finished with necessary white beach or white cedar lippings, mouldings, etc. Special 6" drawer to be made for the cash with dividers of 12 mm plywood. the front of the drawer made out of 18mm blockboard finished with 1.0 mm laminate, sides 12 mm th. plywood and bottom to be made of 6 mm plywood. the inside and sides of the drawer to be duly polished. The drawers and shutters to be provided with necessary drawer sliding channels, hinges, locks etc. A leg rest to be provided made out of 18 mm thk. blockboard duly polished. Inside of the unit to be polished in the matching tone. All visible areas to be covered with beach or cedar lippings, mouldings with reddish brown colour polish. Wire manager, CPU trolley, keyboard tray to be provided. 4" ht. laminated skirting to be provided in all visible ares and 12 mm thk. x 18" wide Plain Glass to be provided at counter top customer face horizontally at 3'-9" lvl. The work should be completed as per specification. Cash counter --- 5 rft Open counter --12 rft (spec. same as above).	2.00	Nos		
	PART C : RESIDULE EXPENDITURE				
7	LOOSE FURNITURE				
A	GENERAL BANKING				
i	Cheque Deposit Box / Suggestion box	1.00	Nos.		
ii	Brochure racks (2' 0" x 16") with acrylic box for brochures.	1.00	Nos.		
iii	WRITING LEDGE	1.00	Nos.		
	Finish. (size - 5" x 5" x 5' 0" MIN.)				
B	MISCELLANEOUS				
i	Roller Blinds	-	Sq.ft		
ii	Notice Board/ Soft Board/Pinup Board	30.00	Sq.ft		
iii	Sand witch poster frames of size 2'0"X3'0"	-	Nos		
iv	CPU Trolley	-	Nos		
	GRAND TOTAL				

